


# Przyłącze Proste Z Uszczelnieniem Typ: Ba. 19



Kategoria: **Przyłącza**

## Dane Techniczne

Nr Katalogowy	Ø R Mm	Ø R Cal	Ø R-Unf Jic 37° Cal	Ø R2 Bspc Cal	B Mm	C Mm	C2 Mm	Ch Mm	Ciśnienie Pracy Bar
Ba.19.04.02	6	1/4'	7/16'	1/8'	28,7	14	6,3	16	350
Ba.19.04.04	6	1/4'	7/16'	1/4'	32	14	9,5	19	350
Ba.19.04.06	6	1/4'	7/16'	3/8'	33	14	9,5	22	350
Ba.19.04.08	6	1/4'	7/16'	1/2'	38,6	14	13	30	350
Ba.19.05.02	8	5/16'	1/2'	1/8'	28,7	14	6,3	16	350
Ba.19.05.04	8	5/16'	1/2'	1/4'	32	14	9,5	19	350
Ba.19.05.06	8	5/16'	1/2'	3/8'	33,7	14	9,5	22	350
Ba.19.06.02	10	3/8'	9/16'	1/8'	28,7	14,1	6,3	16	350
Ba.19.06.04	10	3/8'	9/16'	1/4'	32	14,1	9,5	19	350
Ba.19.06.06	10	3/8'	9/16'	3/8'	33	14,1	9,5	22	350
Ba.19.06.08	10	3/8'	9/16'	1/2'	38,6	14,1	13	30	350
Ba.19.08.04	12	1/2'	3/4'	1/4'	35	16,7	9,5	19	350
Ba.19.08.06	12	1/2'	3/4'	3/8'	36	16,7	9,5	22	350
Ba.19.08.08	12	1/2'	3/4'	1/2'	41,4	16,7	13	30	350
Ba.19.08.12	12	1/2'	3/4'	3/4'	42,4	16,7	13	36	250
Ba.19.10.06	14	-	7/8'	3/8'	39,1	19,3	9,5	24	350
Ba.19.10.06	15	-	7/8'	3/8'	39,1	19,3	9,5	24	350
Ba.19.10.06	16	5/8'	7/8'	3/8'	39,1	19,3	9,5	24	350
Ba.19.10.08	14	-	7/8'	1/2'	43,9	19,3	13	30	350
Ba.19.10.08	15	-	7/8'	1/2'	43,9	19,3	13	30	350
Ba.19.10.08	16	5/8'	7/8'	1/2'	43,9	19,3	13	30	350
Ba.19.10.12	14	-	7/8'	3/4'	43,9	19,3	13	36	250
Ba.19.10.12	15	-	7/8'	3/4'	43,9	19,3	13	36	250

Ba.19.10.12	16	5/8'	7/8'	3/4'	43,9	19,3	13	36	250
Ba.19.12.06	18	-	1 1/16'	3/8'	42,4	21,9	9,5	30	350
Ba.19.12.06	20	3/4'	1 1/16'	3/8'	42,4	21,9	9,5	30	350
Ba.19.12.08	18	-	1 1/16'	1/2'	46,7	21,9	13	30	350
Ba.19.12.08	20	3/4'	1 1/16'	1/2'	46,7	21,9	13	30	350
Ba.19.12.12	18	-	1 1/16'	3/4'	47,5	21,9	13	36	250
Ba.19.12.12	20	3/4'	1 1/16'	3/4'	47,5	21,9	13	36	250
Ba.19.12.16	18	-	1 1/16'	1'	52,6	21,9	16	46	250
Ba.19.12.16	20	3/4'	1 1/16'	1'	52,6	21,9	16	46	250
Ba.19.16.12	25	1'	1 5/16'	3/4'	48,5	23,1	13	36	250
Ba.19.16.16	25	1'	1 5/16'	1'	53,6	23,1	16	46	250
Ba.19.16.20	25	1'	1 5/16'	1 1/4'	55,1	23,1	16	50	175
Ba.19.16.24	25	1'	1 5/16'	1 1/2'	55,7	23,1	16	60	175
Ba.19.20.16	30	-	1 5/8'	1'	53,6	24,3	16	46	210
Ba.19.20.16	32	1 1/4'	1 5/8'	1'	53,6	24,3	16	46	210
Ba.19.20.20	30	-	1 5/8'	1 1/4'	56,9	24,3	16	50	175
Ba.19.20.20	32	1 1/4'	1 5/8'	1 1/4'	56,9	24,3	16	50	175
Ba.19.20.24	30	-	1 5/8'	1 1/2'	56,8	24,3	16	60	140
Ba.19.20.24	32	1 1/4'	1 5/8'	1 1/2'	56,8	24,3	16	60	140
Ba.19.24.16	38	1 1/2'	1 7/8'	1'	57,5	27,5	16	50	140
Ba.19.24.20	38	1 1/2'	1 7/8'	1 1/4'	60,4	27,5	16	50	140
Ba.19.24.24	38	1 1/2'	1 7/8'	1 1/2'	61	27,5	16	60	140