




Przyłącze Proste Typ: Tn 92

Liczba wariantów: **24**



ZESKANUJ MNIE

Warianty produktu

Seria	rednica rury d1 (mm)	Ciśnienie pracy PN (bar)	I (mm)	L (mm)	L1 (mm)	CH1 (mm)	R F (cal)	R N (mm)	R CH2 (mm)	R Numer zamówieniowy	M F mm	M N (mm)
L	6	315	8	23	8,5	14	1/8'	14	14	TN92-6LR	10x1	14
L	8	315	12	25	10	17	1/4'	18	19	TN92-8LR	12x1,5	17
L	8	315	12	26	11,5	17	3/8'	22	22	TN92-8LR3/8'	-	-
L	10	315	12	26	11	19	1/4'	18	19	TN92-10LR	14x1,5	19
L	10	315	12	27	12,5	19	3/8'	22	22	TN92-10LR3/8'	-	-
L	12	315	12	27	12	22	1/4'	18	19	TN92-12LR1/4'	-	-
L	12	315	12	27	12,5	22	3/8'	22	22	TN92-12LR	16x1,5	21
L	12	315	14	28	13	22	1/2'	26	27	TN92-12LR1/2'	-	-
L	15	315	14	29	14	27	1/2'	26	27	TN92-15LR	18x1,5	23
L	18	315	14	31	14,5	32	1/2'	26	27	TN92-18LR	22x1,5	27
L	22	160	16	33	16,5	36	3/4'	32	32	TN92-22LR	26x1,5	31
L	28	160	18	34	17,5	41	1'	39	41	TN92-28LR	33x2	39
L	35	160	20	39	17,5	50	1 1/4'	49	50	TN92-35LR	42x2	49

Seria	rednica rury d1 (mm)	Ciśnienie pracy PN (bar)	I (mm)	L (mm)	L1 (mm)	CH1 (mm)	R F (cal)	R N (mm)	R CH2 (mm)	R Numer zamówieniowy	M F mm	M N (mm)
L	42	160	22	42	19	60	1 1/2'	55	55	TN92-42LR	48 x 2	55
S	6	630	12	28	13	17	1/4'	18	19	TN92-6SR	12x1,5	17
S	8	630	12	30	15	19	1/4'	18	19	TN92-8SR	14x1,5	19
S	10	630	12	31	15	22	3/8'	22	22	TN92-10SR	16x1,5	21
S	12	630	12	33	17	24	3/8'	22	22	TN92-12SR	18x1,5	23
S	12	630	14	34	17,5	24	1/2'	26	27	TN92-12SR1/2'	-	-
S	14	630	14	37	19	27	1/2'	26	27	TN92-14SR	20x1,5	25
S	16	400	14	37	18,5	30	1/2'	26	27	TN92-16SR	22x1,5	27
S	20	400	16	42	20,5	36	3/4'	32	32	TN92-20SR	27x2	32
S	25	400	18	47	23	46	1'	39	41	TN92-25SR	33x2	39
S	30	250	20	50	23,5	50	1 1/4'	49	50	TN92-30SR	42x2	49