



Przyłącze Kątowe Typ: Tn 94

Liczba wariantów: **26**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy R	Nr katalogowy M	Nr katalogowy NPT	Seria	Ø d1 mm	Ciśnienie pracy bar	Ø F2 cal R	Ø F2 mm M	Ø F2 cal NPT	I mm	L mm	L1 mm	L2 mm	CH1 mm	CH2 mm	Waga 100 szt. Kg
TN94-4LLR	TN94-4LLM	TN94-4LLNPT	LL	4	100	1/8'	8x1	1/8'	8	21	11	17	10	9	2
TN94-5LLR	TN94-5LLM	TN94-5LLNPT	LL	5	100	1/8'	8x1	1/8'	8	21	9,5	17	12	9	2
TN94-6LLR	TN94-6LLM	TN94-6LLNPT	LL	6	100	1/8'	10x1	1/8'	8	21	9,5	17	12	9	2
TN94-8LLR	TN94-8LLM	TN94-8LLNPT	LL	8	100	1/8'	10x1	1/8'	8	23	11,5	20	14	12	2,5
TN94-10LLR	-	-	LL	10	100	1/4'	-	-	12	27	15	25	17	14	3,5
TN94-12LLR	-	-	LL	12	100	1/4'	-	-	12	25	13	23	19	17	5
TN94-6LR	TN94-6LM	TN94-6LNPT	L	6	315	1/8'	10x1	1/8'	8	27	12	20	14	12	3,5
TN94-8LR	TN94-8LM	TN94-8LNPT	L	8	315	1/4'	12x1,5	1/4'	12	29	14	26	17	12	5
TN94-10LR	TN94-10LM	TN94-10LNPT	L	10	315	1/4'	14x1,5	1/4'	12	30	15	27	19	14	6
TN94-12LR	TN94-12LM	TN94-12LNPT	L	12	315	3/8'	16x1,5	3/8'	12	32	17	28	22	17	8,5
TN94-15LR	TN94-15LM	TN94-15LNPT	L	15	315	1/2'	18x1,5	1/2'	14	36	21	34	27	19	14,5
TN94-18LR	TN94-18LM	TN94-18LNPT	L	18	315	1/2'	22x1,5	1/2'	14	40	23,5	36	32	24	17
TN94-22LR	-	TN94-22LNPT	L	22	160	3/4'	-	3/4'	16	44	27,5	42	36	27	23,5
TN94-28LR	-	TN94-28LNPT	L	28	160	1'	-	1'	18	47	30,5	48	41	36	37,5
TN94-35LR	-	TN94-35LNPT	L	35	160	1 1/4'	-	1 1/4'	20	56	34,5	54	50	41	57

Nr katalogowy R	Nr katalogowy M	Nr katalogowy NPT	Seria	Ø d1 mm	Ciśnienie pracy bar	Ø F2 cal R	Ø F2 mm M	Ø F2 cal NPT	I mm	L mm	L1 mm	L2 mm	CH1 mm	CH2 mm	Waga 100 szt. Kg
TN94-42LR	-	TN94-42LNPT	L	42	160	1 1/2'	-	1 1/2'	22	63	40	61	60	50	83
TN94-6SR	TN94-6SM	TN94-6SNPT	S	6	630	1/4'	12x1,5	1/4'	12	31	16	26	17	12	5,5
TN94-8SR	TN94-8SM	TN94-8SNPT	S	8	630	1/4'	14x1,5	1/4'	12	32	17	27	19	14	7,2
TN94-10SR	TN94-10SM	TN94-10SNPT	S	10	630	3/8'	16x1,5	3/8'	12	34	17,5	28	22	17	10,3
TN94-12SR	TN94-12SM	TN94-12SNPT	S	12	630	3/8'	18x1,5	3/8'	12	38	21,5	31	24	17	11
TN94-14SR	TN94-14SM	TN94-14SNPT	S	14	630	1/2'	20x1,5	1/2'	14	40	22	32	27	19	16
TN94-16SR	TN94-16SM	TN94-16SNPT	S	16	400	1/2'	22x1,5	1/2'	14	43	24,5	32	30	24	19,5
TN94-20SR	-	TN94-20SNPT	S	20	400	3/4'	-	3/4'	16	48	26,5	42	36	27	30,3
TN94-25SR	-	TN94-25SNPT	S	25	400	1'	-	1'	18	54	30	48	46	36	57
TN94-30SR	-	TN94-30SNPT	S	30	400	1 1/4'	-	1 1/4'	20	62	35,5	54	50	41	83
TN94-38SR	-	TN94-38SNPT	S	38	315	1 1/2'	-	1 1/2'	22	72	41	61	60	50	117