




Złącze Kątowe Typ: Tn 99

Liczba wariantów: 25



ZESKANUJ MNIE

Warianty produktu

Numer zamówieniowy	Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	L mm	L1 mm	CH1 mm	CH2 mm	Waga 100 szt. kg
1AX099LL04	LL	4	100	21	11,0	10	9	2,0
1AX099LL06	LL	6	100	21	9,5	12	9	2,2
1AX099LL08	LL	8	100	23	11,5	14	12	3,9
1AX099LL10	LL	10	100	27	15,0	17	14	5,2
1AX099LL12	LL	12	100	25	13,0	19	17	7,0
1BX099LO06	L	6	315	27	12,0	14	12	4,2
1BX099LO08	L	8	315	29	14,0	17	12	5,8
1BX099LO10	L	10	315	30	15,0	19	14	7,7
1BX099LO12	L	12	315	32	17,0	22	17	9,8
1BX099LO15	L	15	315	36	21,0	27	19	16,0
1BX099LO18	L	18	315	40	23,5	32	24	24,0
1BX099LO22	L	22	160	44	27,5	36	27	32,0
1BX099LO28	L	28	160	47	30,5	41	36	42,4

Numer zamówieniowy	Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	L mm	L1 mm	CH1 mm	CH2 mm	Waga 100 szt. kg
IBX099LO35	L	35	160	56	34,5	50	41	76,5
IBX099LO42	L	42	160	63	40,0	60	50	109,0
IBX099SO06	S	6	630	31	16,0	17	12	7,1
IBX099SO08	S	8	630	32	17,0	19	14	8,1
IBX099SO10	S	10	630	34	17,5	22	17	12,9
IBX099SO12	S	12	630	38	21,5	24	17	15,0
IBX099SO14	S	14	630	40	22,0	27	19	21,0
IBX099SO16	S	16	400	43	24,5	30	24	26,0
IBX099SO20	S	20	400	48	26,5	36	27	42,0
IBX099SO25	S	25	400	54	30,0	46	36	78,0
IBX099SO30	S	30	400	62	35,5	50	41	99,0
IBX099SO38	S	38	315	72	41,0	60	50	133,0