



Trójnik Redukcyjny Odmiana Ciężka Typ: Tn 100R-S

Liczba wariantów: 17



ZESKANUJ MNIE

Warianty produktu

Numer zamówieniowy	Seria	Średnica rury d1 mm	Średnica rury d2 mm	Średnica rury d3 mm	Ciśnienie pracy PN bar	L1 mm	L2 mm	L3 mm	L4 mm	L5 mm	L6 mm	CH1 mm	CH2 mm	CH3 mm	CH4 mm
IBX100S100610	S	10	6	10	630	34	32,5	34	17,5	17,5	17,5	22	17	22	17
IBX100S120808	S	12	8	8	630	38	36,5	36,5	21,5	21,5	21,5	24	19	19	17
IBX100S120812	S	12	8	12	630	38	36,5	38	21,5	21,5	21,5	24	19	24	17
IBX100S121012	S	12	10	12	630	38	38	38	21,5	21,5	21,5	24	22	24	17
IBX100S121612	S	12	16	12	400	41	43	41	24,5	24,5	24,5	24	30	24	24
IBX100S160616	S	16	6	16	400	43	40	43	24,5	24,5	24,5	30	17	30	24
IBX100S160816	S	16	8	16	400	43	40	43	24,5	24,5	24,5	30	19	30	24
IBX100S161016	S	16	10	16	400	43	41	43	24,5	24,5	24,5	30	22	30	24
IBX100S161216	S	16	12	16	400	43	41	43	24,5	24,5	24,5	30	24	30	24
IBX100S162016	S	16	20	16	400	45	48	45	26,5	26,5	26,5	30	36	30	27
IBX100S201020	S	20	10	20	400	48	43	48	26,5	26,5	26,5	36	22	36	27
IBX100S201220	S	20	12	20	400	48	43	48	26,5	26,5	26,5	36	24	36	27
IBX100S201620	S	20	16	20	400	48	45	48	26,5	26,5	26,5	36	30	36	27
IBX100S202520	S	20	25	20	400	51,5	54	51,5	30	30	30	36	46	36	36
IBX100S251625	S	25	16	25	400	54	49	54	30	30	30	46	30	46	36
IBX100S252025	S	25	20	25	400	54	52	54	30	30	30	46	36	46	36

Numer zamówieniowy	Seria	Średnica rury d1 mm	Średnica rury d2 mm	Średnica rury d3 mm	Ciśnienie pracy PN bar	L1 mm	L2 mm	L3 mm	L4 mm	L5 mm	L6 mm	CH1 mm	CH2 mm	CH3 mm	CH4 mm
IBX100S253025	S	25	30	25	400	60	62	60	35,5	35,5	35,5	46	50	46	41