



Złącze Grodziowe Typ: Tn 102

Liczba wariantów: **20**



ZESKANUJ MNIE

Warianty produktu

Numer zamówieniowy	Seria	Śr. rury d1 mm	Ciś. pracy PN bar	L1 mm	L2 mm	L3 mm	L4 mm	CH1 mm	CH2 mm	CH4 mm	Waga 100 szt. kg
1S-102LO06	L	6	315	22,0	27,0	7,0	42,0	14,0	17,0	17,0	7,0
1S-102LO08	L	8	315	23	27	8	42	17	19,0	19,0	8.5
1S-102LO10	L	10	315	25	28	10	43	19	22,0	22,0	12.7
1S-102LO12	L	12	315	25	29	10	44	22	24,0	24,0	15.0
1S-102LO15	L	15	315	27	31	12	46	27	30,0	27,0	23.0
1S-102LO18	L	18	315	30	32,5	13,5	49	32	36,0	32,0	33.0
1S-102LO22	L	22	160	33	34,5	16,5	51	36	41,0	36,0	41.0
1S-102LO28	L	28	160	35	35,5	18,5	52	41	46,0	41,0	53.0
1S-102LO35	L	35	160	40	36,5	18,5	58	50	55,0	50,0	80.0
1S-102LO42	L	42	160	42	36	19	59	60	65,0	60,0	120.0
1S-102SO06	S	6	630	27	29	12	44	17	19,0	19,0	10.0
1S-102SO08	S	8	630	28	29,	13,0	44	19	22,0	22,0	13.0

Numer zamówieniowy	Seria	Śr. rury d1 mm	Ciś. pracy PN bar	L1 mm	L2 mm	L3 mm	L4 mm	CH1 mm	CH2 mm	CH4 mm	Waga 100 szt. kg
IS-102SO10	S	10	630	31	29,5	14,5	46	22	24,0	24.0	19.0
IS-102SO12	S	12	630	31	30,5	14,5	47	24	27,0	27.0	22.0
IS-102SO14	S	14	630	35	32,0	17	50	27	30,0	30.0	27.0
IS-102SO16	S	16	400	35	31,5	16,5	50	30	32,0	32.0	32.0
IS-102SO20	S	20	400	39	33,5	17,5	55	36	41,0	41.0	55.0
IS-102SO25	S	25	400	44	35	20	59	46	46,0	46.0	91.0
IS-102SO30	S	30	400	48	37,5	21,5	64	50	50,0	50.0	110.0
IS-102SO38	S	38	315	53	37	22	68	60	65,0	65.0	150.0