



Złącze Grodziowe Kątowe Typ: Tn 118

Liczba wariantów: 20



ZESKANUJ MNIE

Warianty produktu

Numer zamówieniowy	Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	L mm	L1 mm	L2 mm	L3 mm	L4 mm	N mm	CH1 mm	CH2 mm	CH3 mm	Waga 100 szt. kg
1S-118LO06	L	6	315	27	12	27	14	42	17	14	17	12	7
1S-118LO08	L	8	315	29	14	27	17	42	19	17	19	12	10
1S-118LO10	L	10	315	30	15	28	18	43	22	19	22	14	13
1S-118LO12	L	12	315	32	17	29	20	44	24	22	24	17	19
1S-118LO15	L	15	315	36	21	31	23	46	27	27	30	19	28
1S-118LO18	L	18	315	40	23,5	32,5	24	49	32	32	36	24	38
1S-118LO22	L	22	160	44	27,5	34,5	30	51	36	36	41	27	49
1S-118LO28	L	28	160	47	30,5	35,5	34	52	42	41	46	36	70
1S-118LO35	L	35	160	56	34,5	36,5	39	58	50	50	55	41	103
1S-118LO42	L	42	160	63	40	36	43	59	60	60	65	50	160
1S-118SO06	S	6	630	31	16	29	17	44	19	17	19	12	10
1S-118SO08	S	8	630	32	17	29	18	44	22	19	22	14	13
1S-118SO10	S	10	630	34	17,5	29,5	20	46	24	22	24	17	20

Numer zamówieniowy	Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	L mm	L1 mm	L2 mm	L3 mm	L4 mm	N mm	CH1 mm	CH2 mm	CH3 mm	Waga 100 szt. kg
1S-118SO12	S	12	630	38	21,5	30,5	21	47	27	24	27	17	24
1S-118SO14	S	14	630	40	22	32	23	50	27	27	30	19	30
1S-118SO16	S	16	400	43	24,5	31,5	24	50	30	30	32	24	37
1S-118SO20	S	20	400	48	26,5	33,5	30	55	36	36	41	27	60
1S-118SO25	S	25	400	54	30	35	34	59	42	46	46	36	108
1S-118SO30	S	30	400	62	35,5	37,5	39	64	50	50	50	41	120
1S-118SO38	S	38	315	72	41	37	43	68	60	60	65	50	180