



Trójnik Z Nakrętką W Przeciwpzeciecie Typ: Tn 120

Liczba wariantów: 21



ZESKANUJ MNIE

Warianty produktu

Numer zamówieniowy	Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	L mm	L1 mm	L2 mm	D1 mm	F1 mm	CH1 mm	CH2 mm	Waga 100 szt. kg
TN120-6L	L	6	315	27	12	26	6	12x1,5	14	12	5,6
TN120-8L	L	8	315	29	14	27,5	8	14x1,5	17	12	6,6
TN120-10L	L	10	315	30	15	29	10	16x1,5	19	14	9
TN120-12L	L	12	315	32	17	29,5	12	18x1,5	22	17	13
TN120-15L	L	15	315	36	21	32,5	15	22x1,5	27	19	20,9
TN120-18L	L	18	315	40	23,5	35,5	18	26x1,5	32	24	32
TN120-22L	L	22	160	44	27,5	38,5	22	30x2	36	27	42
TN120-28L	L	28	160	47	30,5	41,5	28	36x2	41	36	60
TN120-35L	L	35	160	56	34,5	51	35	45x2	50	41	92,5
TN120-42L	L	42	160	63	40	60	42	52x2	60	50	136
TN120-6S	S	6	630	31	16	27	6	14x1,5	17	12	8,6
TN120-8S	S	8	630	32	17	27,5	8	16x1,5	19	14	11,9
TN120-10L	S	10	630	34	17,5	30	10	18x1,5	22	17	14

Numer zamówieniowy	Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	L mm	L1 mm	L2 mm	D1 mm	F1 mm	CH1 mm	CH2 mm	Waga 100 szt. kg
TN120-20S	S	12	630	38	21,5	31	12	20x1,5	24	17	19,8
TN120-14S	S	14	630	40	22	35	14	22x1,5	27	19	27
TN120-16S	S	16	400	43	24,5	36,5	16	24x1,5	30	24	36,5
TN120-20S	S	20	400	48	26,5	44,5	20	30x2	36	27	54
TN120-20S	S	20	400	48	26,5	44,5	20	30x2	36	27	54
TN120-25S	S	25	400	54	30	50	25	36x2	46	36	102
TN120-30S	S	30	400	62	35,5	55	30	42x2	50	41	133
TN120-38S	S	38	315	72	41	64,5	38	52x2	60	50	210