



Złącze Banjo Stalowe Z Uszczelnieniem Typ: Tn 111 Gg R

Liczba wariantów: 20



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	I mm	L mm	L10 mm	L11 mm	L12 mm	Ø N mm	CH1 mm	CH2 mm	CH mm	Ø F cal	Waga 100 szt. kg
1S-IIIIGGRLO06	L	6	315	8	28	13	12	27	15	14	17	19	1/8'	6,5
1S-IIIIGGRLO08	L	8	315	12	29	14,5	14,5	30,5	19	17	19	22	1/4'	10,5
1S-IIIIGGRLO10	L	10	315	12	30,5	15,5	14,5	30,5	19	19	19	22	1/4'	12
1S-IIIIGGRLO12	L	12	315	12	34,5	19,5	17	37,5	23	22	24	30	3/8'	20
1S-IIIIGGRLO15	L	15	315	14	38	22	21,5	47	27	27	27	32	1/2'	33
1S-IIIIGGRLO18	L	18	315	14	39,5	22	21,5	47,5	27	32	27	36	1/2'	35
1S-IIIIGGRLO22	L	22	160	16	46	28	24,5	55,5	33	36	32	41	3/4'	56
1S-IIIIGGRLO28	L	28	160	18	50	31,5	30,5	68	40	41	41	50	1'	93,5
1S-IIIIGGRLO35	L	35	160	20	59	35,5	35,5	79	50	50	50	60	1 1/4'	152
1S-IIIIGGRLO42	L	42	160	22	66	41,5	40,5	90	56	60	55	70	1 1/2'	234
1S-IIIIGGRSO06	S	6	400	12	31	16,5	14,5	30,5	19	17	19	22	1/4'	10,5
1S-IIIIGGRSO08	S	8	400	12	31	16,5	14,5	30,5	19	19	19	22	1/4'	13
1S-IIIIGGRSO10	S	10	400	12	36,5	20	17	37,5	23	22	24	30	3/8'	22,5

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	I mm	L mm	L10 mm	L11 mm	L12 mm	Ø N mm	CH1 mm	CH2 mm	CH mm	Ø F cal	Waga 100 szt. kg
1S-IIIIGGRSO12	S	12	400	12	36,5	20	17	37,5	23	24	24	30	3/8'	23
1S-IIIIGGRSO14	S	14	400	14	42,5	23,5	21,5	47,5	27	27	27	36	1/2'	36,5
1S-IIIIGGRSO16	S	16	400	14	42,5	23,5	21,5	47,5	27	30	27	36	1/2'	36,5
1S-IIIIGGRSO20	S	20	400	16	51	27	24,5	55,5	33	36	32	41	3/4'	64
1S-IIIIGGRSO25	S	25	250	18	58	31	30,5	68	40	46	41	50	1'	113,5
1S-IIIIGGRSO30	S	30	250	20	66	36,5	35,5	79	50	50	50	60	1 1/4'	173
1S-IIIIGGRSO38	S	38	250	22	76	42,5	40,5	90	56	60	55	70	1 1/2'	271