




Przyłącze Proste Typ: Tn 126 A-R

Liczba wariantów: **20**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	Ø F cal	Ø D mm	I mm	Ø N mm	Ø F1 mm	CH1 mm	CH2 mm	Waga 100 szt. kg
TN126A-6LR	L	6	315	32,5	1/8'	6	8	14	12x1,5	14	14	2,5
TN126A-8LR	L	8	315	41,5	1/4'	8	12	18	14x1,5	17	19	3,9
TN126A-10LR	L	10	315	39,5	1/4'	10	12	18	16x1,5	19	19	4,9
TN126A-12LR	L	12	315	46	3/8'	12	12	22	18x1,5	22	22	6,4
TN126A-15LR	L	15	315	46	1/2'	15	14	26	22x1,5	27	27	11,5
TN126A-18LR	L	18	315	45,5	1/2'	18	14	26	26x1,5	32	27	13,8
TN126A-22LR	L	22	160	48,5	3/4'	22	16	32	30x2	36	32	17,5
TN126A-28LR	L	28	160	53	1'	28	18	39	36x2	41	41	24,8
TN126A-35LR	L	35	160	62,5	1 1/4'	35	20	49	45x2	50	50	40,7
TN126A-42LR	L	42	160	68,5	1 1/2'	42	22	55	52x2	60	55	52,7
TN126A-6SR	S	6	630	39	1/4'	6	12	18	14x1,5	17	19	5
TN126A-8SR	S	8	630	41,5	1/4'	8	12	18	16x1,5	19	19	5,5
TN126A-10SR	S	10	630	44	3/8'	10	12	22	18x1,5	22	22	8,2

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	Ø F cal	Ø D mm	I mm	Ø N mm	Ø F1 mm	CH1 mm	CH2 mm	Waga 100 szt. kg
TN126A-12SR	S	12	630	46	3/8'	12	12	22	20x1,5	24	22	9,5
TN126A-14SR	S	14	630	50,5	1/2'	14	14	26	22x1,5	27	27	14,5
TN126A-16SR	S	16	400	51	1/2'	16	14	26	24x1,5	30	27	15,8
TN126A-20SR	S	20	400	59	3/4'	20	16	32	30x2	36	32	25,3
TN126A-25SR	S	25	400	66	1'	25	18	39	36x2	46	41	46,5
TN126A-30SR	S	30	250	71	1 1/4'	30	20	49	42x2	50	50	64,5
TN126A-38SR	S	38	250	82	1 1/2'	38	22	55	52x2	60	55	89