



Przyłącze Proste Typ: Tn 126 A-M

Liczba wariantów: **20**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	Ø F mm	Ø D mm	I mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	Waga 100 szt. kg
TNI26A-6LM	L	6	315	32,5	10x1	6	8	14	14	12x1,5	14	2,5
TNI26A-8LM	L	8	315	38,5	12x1,5	8	12	17	17	14x1,5	17	3,9
TNI26A-10LM	L	10	315	39,5	14x1,5	10	12	19	19	16x1,5	19	4,9
TNI26A-12LM	L	12	315	42,5	16x1,5	12	12	22	21	18x1,5	22	6,4
TNI26A-15LM	L	15	315	43,5	18x1,5	15	12	24	23	22x1,5	27	9,8
TNI26A-18LM	L	18	315	45,5	22x1,5	18	14	27	27	26x1,5	32	13
TNI26-22LM	L	22	160	48,5	26x1,5	22	16	32	31	30x2	36	17,5
TNI26-28LM	L	28	160	53	33x2	28	18	41	39	36x2	41	24,8
TNI26A-35LM	L	35	160	62,5	42x2	35	20	50	49	45x2	50	40,7
TNI26A-42LM	L	42	160	68,5	48x2	42	22	55	55	52x2	60	46
TNI26A-6SM	S	6	630	39	12x1,5	6	12	17	17	14x1,5	17	4,6
TNI26A-8SM	S	8	630	41,5	14x1,5	8	12	19	19	16x1,5	19	5,5

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	Ø F mm	Ø D mm	I mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	Waga 100 szt. kg
TNI26A-10SM	S	10	630	44	16x1,5	10	12	22	21	18x1,5	22	8,2
TNI26A-12SM	S	12	630	46	18x1,5	12	12	24	23	20x1,5	24	10,4
TNI26A-14SM	S	14	630	50,5	20x1,5	14	14	27	25	22x1,5	27	14,5
TNI26A-16SM	S	16	400	51	22x1,5	16	14	27	27	24x1,5	30	15,8
TNI26A-20SM	S	20	400	59	27x2	20	16	32	32	30x2	36	25,3
TNI26A-25SM	S	25	400	66	33x2	25	18	41	39	36x2	46	46,5
TNI26A-30SM	S	30	250	71	42x2	30	20	50	49	42x2	50	64,5
TNI26A-38SM	S	38	250	82	48x2	38	22	55	55	52x2	60	89