



Przyłącze Proste Z Uszczelnieniem Typ: Tn 126 Gg-R, Tn 126A Gg-R

Liczba wariantów: 20



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	Ø F cal	Ø D1 mm	I mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	Waga 100 szt. TN 126 GG-R kg	Waga 100 szt. TN 126A GG-R kg
TN126GG-6LR	TN126AGG-6LR	L	6	315	32,5	1/8'	6	8	14	14	12x1,5	14	1,5	2,5
TN126GG-8LR	TN126AGG-8LR	L	8	315	41,5	1/4'	8	12	19	19	14x1,5	17	2,5	4,3
TN126GG-10LR	TN126AGG-10LR	L	10	315	39,5	1/4'	10	12	19	19	16x1,5	19	2,7	4,8
TN126GG-12LR	TN126AGG-12LR	L	12	315	46	3/8'	12	12	22	22	18x1,5	22	3,7	6,4
TN126GG-15LR	TN126AGG-15LR	L	15	315	46	1/2'	15	14	27	27	22x1,5	27	7,2	11,5
TN126GG-18LR	TN126AGG-18LR	L	18	315	45,5	1/2'	18	14	27	27	26x1,5	32	7,5	13,8
TN126GG-22LR	TN126AGG-22LR	L	22	160	48,5	3/4'	22	16	32	32	30x2	36	9	17,5
TN126GG-28LR	TN126AGG-28LR	L	28	160	53	1'	28	18	41	40	36x2	41	15,7	24,8
TN126GG-35LR	TN126AGG-35LR	L	35	160	62,5	1 1/4'	35	20	50	50	45x2	50	26,2	40,7
TN126GG-42LR	TN126AGG-42LR	L	42	160	68,5	1 1/2'	42	22	55	55	52x2	60	29,3	46,3
TN126GG-6SR	TN126AGG-6SR	S	6	630	39	1/4'	6	12	19	19	14x1,5	17	3,5	5
TN126GG-8SR	TN126AGG-8SR	S	8	630	41,5	1/4'	8	12	19	19	16x1,5	19	3,7	5,5
TN126GG-10SR	TN126AGG-10SR	S	10	630	44,5	3/8'	10	12	22	22	18x1,5	22	4,9	8,2

Nr katalogowy	Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	Ø F cal	Ø D1 mm	I mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	Waga 100 szt. TN 126 GG-R kg	Waga 100 szt. TN 126A GG-R kg
TN126GG-12SR	TN126AGG-12SR	S	12	630	46	3/8'	12	12	22	22	20x1,5	24	5,6	9,5
TN126GG-14SR	TN126AGG-14SR	S	14	630	51	1/2'	14	14	27	27	22x1,5	27	9	14,5
TN126GG-16SR	TN126AGG-16SR	S	16	400	50,5	1/2'	16	14	27	27	24x1,5	30	9,4	15,8
TN126GG-20SR	TN126AGG-20SR	S	20	400	59	3/4'	20	16	32	32	30x2	36	15	25,3
TN126GG-25SR	TN126AGG-25SR	S	25	400	66	1'	25	18	41	40	36x2	46	26	46,5
TN126GG-30SR	TN126AGG-30SR	S	30	400	71	1 1/4'	30	20	50	50	42x2	50	41,4	64,5
TN126GG-38SR	TN126AGG-38SR	S	38	315	82	1 1/2'	38	22	55	55	52x2	60	56	89