



Przyłącze Proste Z Uszczelnieniem Typ: Tn 126 Gg-M, Tn 126A Gg-M

Liczba wariantów: 20



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	Ø F mm	Ø D mm	I mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	Waga 100 szt. TN 126 GG-M kg	Waga 100 szt. TN 126A GG-M kg
TN126GG-6LM	TN126AGG-6LM	L	6	315	32,5	10x1	6	8	14	14	12x1,5	14	1,5	2,5
TN126GG-8LM	TN126AGG-8LM	L	8	315	38,5	12x1,5	8	12	17	17	14x1,5	17	2,5	3,9
TN126GG-10LM	TN126AGG-10LM	L	10	315	39	14x1,5	10	12	19	19	16x1,5	19	2,7	4,9
TN126GG-12LM	TN126AGG-12LM	L	12	315	42,5	16x1,5	12	12	22	22	18x1,5	22	3,7	6,4
TN126GG-15LM	TN126AGG-15LM	L	15	315	43,5	18x1,5	15	12	24	24	22x1,5	27	7,2	9,8
TN126GG-18LM	TN126AGG-18LM	L	18	315	45,5	22x1,5	18	14	27	27	26x1,5	32	7,5	13
TN126GG-22LM	TN126AGG-22LM	L	22	160	48,5	26x1,5	22	16	32	32	30x2	36	9	17,5
TN126GG-28LM	TN126AGG-28LM	L	28	160	53,5	33x2	28	18	41	40	36x2	41	15,7	24,8
TN126GG-35LM	TN126AGG-35LM	L	35	160	62,5	42x2	35	20	50	50	45x2	50	26,2	40,7
TN126GG-42LM	TN126AGG-42LM	L	42	160	68,5	48x2	42	22	55	55	52x2	60	29,3	46
TN126GG-6SM	TN126AGG-6SM	S	6	630	39	12x1,5	6	12	17	17	14x1,5	17	3,5	4,6
TN126GG-8SM	TN126AGG-8SM	S	8	630	41,5	14x1,5	8	12	19	19	16x1,5	19	3,7	5,5
TN126GG-10SM	TN126AGG-10SM	S	10	630	44	16x1,5	10	12	22	22	18x1,5	22	4,9	8,2
TN126GG-12SM	TN126GG-12SM	S	12	630	46	18x1,5	12	12	24	24	20x1,5	24	5,6	10,4

Nr katalogowy	Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	Ø F mm	Ø D mm	I mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	Waga 100 szt. TN 126 GG-M kg	Waga 100 szt. TN 126A GG-M kg
TN126GG-14SM	TN126AGG-14SM	S	14	630	50,5	20x1,5	14	14	27	26	22x1,5	27	9	14,5
TN126GG-16SM	TN126AGG-16SM	S	16	400	51	22x1,5	16	14	27	27	24x1,5	30	9,4	15,8
TN126GG-20SM	TN126AGG-20SM	S	20	400	59	27x2	20	16	32	32	30x2	36	15	25,3
TN126GG-25SM	TN126AGG-25SM	S	25	400	66	33x2	25	18	41	40	36x2	46	26	46,5
TN126GG-30SM	TN126AGG-30SM	S	30	400	71	42x2	30	20	50	50	42x2	50	41,4	64,5
TN126GG-38SM	TN126AGG-38SM	S	38	315	82	48x2	38	22	55	55	52x2	60	56	89