



Złącze Proste Z Nakrętką Odmiana Lekka Typ: Tn 132 L

Liczba wariantów: 45



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy TN132	Seria	Ø D1 mm	Ø D2 mm	Ciśnienie pracy bar	L1 mm	L2 mm	CH2 mm	CH3 mm	Ø F1 mm	CH mm	Waga 100 szt. kg TN132	Waga 100 szt. kg TN132A
1B-132AL0806Y	L	8	6	315	29,5	30	14	17	14x1,5	14	2,7	4,1
1B-132AL1006Y	L	10	6	315	29,5	30	14	19	16x1,5	14	2,5	4,8
1B-132AL1008Y	L	10	8	315	29,5	30	17	19	16x1,5	17	3	5,3
1B-132AL1206Y	L	12	6	315	29,5	30	14	22	18x1,5	14	3,3	6
1B-132AL1208Y	L	12	8	315	29,5	30	17	22	18x1,5	17	3,7	6,4
1B-132AL1210Y	L	12	10	315	31	31	19	22	18x1,5	17	4,3	7
1B-132AL1506Y	L	15	6	315	29,5	29	14	27	22x1,5	17	4	8,3
1B-132AL1508Y	L	15	8	315	29,5	29	17	27	22x1,5	17	4,8	9,1
1B-132AL1510Y	L	15	10	315	31	30	19	27	22x1,5	17	5,2	9,5
1B-132AL1512Y	L	15	12	315	31	30	22	27	22x1,5	19	5,9	10,2
1B-132AL1806Y	L	18	6	315	30,5	29	14	32	26x1,5	19	4,7	11
1B-132AL1808Y	L	18	8	315	30,5	29	17	32	26x1,5	19	5	11,3

Nr katalogowy TN132	Seria	Ø D1 mm	Ø D2 mm	Ciśnienie pracy bar	L1 mm	L2 mm	CH2 mm	CH3 mm	Ø F1 mm	CH mm	Waga 100 szt. kg TN132	Waga 100 szt. kg TN132A
1B-132AL1810Y	L	18	10	315	32	30	19	32	26x1,5	19	5,7	12
1B-132AL1812Y	L	18	12	315	32	30	22	32	26x1,5	19	6,4	12,7
1B-132AL1815Y	L	18	15	315	32,5	32	27	32	26x1,5	24	8,8	15,1
1B-132AL2206Y	L	22	6	160	33,5	32	14	36	30x2	24	5,8	14,3
1B-132AL2208Y	L	22	8	160	33,5	32	17	36	30x2	24	6,6	15,1
1B-132AL2210Y	L	22	10	160	35	33	19	36	30x2	24	6,8	15,3
1B-132AL2212Y	L	22	12	160	35	33	22	36	30x2	24	7,7	16,2
1B-132AL2215Y	L	22	15	160	35,5	35	27	36	30x2	24	9,7	18,2
1B-132AL2218Y	L	22	18	160	35	35	32	36	30x2	27	11,5	20
1B-132AL2806Y	L	28	6	160	34,5	33	14	41	36x2	32	9,6	18,7
1B-132AL2808Y	L	28	8	160	34,5	33	17	41	36x2	32	10,4	19,5
1B-132AL2810Y	L	28	10	160	36	34	19	41	36x2	32	11,1	20,2
1B-132AL2812Y	L	28	12	160	36	34	22	41	36x2	32	11,6	20,7
1B-132AL2815Y	L	28	15	160	36,5	35	27	41	36x2	32	13,6	22,7

Nr katalogowy TN132	Seria	Ø D1 mm	Ø D2 mm	Ciśnienie pracy bar	L1 mm	L2 mm	CH2 mm	CH3 mm	Ø F1 mm	CH mm	Waga 100 szt. kg TN132	Waga 100 szt. kg TN132A
1B-132AL2818Y	L	28	18	160	36	36	32	41	36x2	32	15,6	24,7
1B-132AL2822Y	L	28	22	160	36	38	36	41	36x2	32	17,9	27
1B-132AL3506Y	L	35	6	160	40,5	34	14	50	45x2	36	16,5	31
1B-132AL3508Y	L	35	8	160	40,5	34	17	50	45x2	36	16,9	31,4
1B-132AL3510Y	L	35	10	160	42	35	19	50	45x2	36	17,7	32,2
1B-132AL3512Y	L	35	12	160	42	35	22	50	45x2	36	17,7	32,2
1B-132AL3515Y	L	35	15	160	42,5	36	27	50	45x2	36	20,5	35
1B-132AL3518Y	L	35	18	160	42	37	32	50	45x2	36	21,9	36,4
1B-132AL3522Y	L	35	22	160	44	39	36	50	45x2	36	23,5	38
1B-132AL3528Y	L	35	28	160	44	39	41	50	45x2	41	25,2	39,7
1B-132AL4206Y	L	42	6	160	42,5	35	14	60	52x2	46	21,2	44,2
1B-132AL4208Y	L	42	8	160	42,5	35	17	60	52x2	46	22,2	45,2
1B-132AL4210Y	L	42	10	160	44	36	19	60	52x2	46	22,2	45,2
1B-132AL4212Y	L	42	12	160	43	36	22	60	52x2	46	23,1	46,1

Nr katalogowy TN132	Seria	Ø D1 mm	Ø D2 mm	Ciśnienie pracy bar	L1 mm	L2 mm	CH2 mm	CH3 mm	Ø F1 mm	CH mm	Waga 100 szt. kg TN132	Waga 100 szt. kg TN132A
1B-132AL4215Y	L	42	15	160	44,5	37	27	60	52x2	46	24,2	47,2
1B-132AL4218Y	L	42	18	160	44	38	32	60	52x2	46	26,1	49,1
1B-132AL4222Y	L	42	22	160	46	40	36	60	52x2	46	28,2	51,2
1B-132AL4228Y	L	42	28	160	46	40	41	60	52x2	46	30,2	53,2
1B-132AL4235Y	L	42	35	160	45	44	50	60	52x2	46	35,5	58,5