




Złącze Kątowe Z Nakrętką Typ: Tn 419

Liczba wariantów: **20**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	L1 mm	L2 mm	Ø F1 mm	CH1 mm	CH2 mm	O-Ring mm	Waga 100 szt. kg
1B-419LO06Y	L	6	315	27	12	26	12x1,5	14	12	4x1,5	4
1B-419LO08Y	L	8	315	29	14	27,5	14x1,5	17	12	6x1,5	5,5
1B-419LO10Y	L	10	315	30	15	29	16x1,5	19	14	7,5x1,5	7
1B-419LO12Y	L	12	315	32	17	29,5	18x1,5	22	17	9x1,5	9,5
1B-419LO15Y	L	15	315	36	21	32,5	22x1,5	27	19	12x2	16,5
1B-419LO18Y	L	18	315	40	23,5	35,5	26x1,5	32	24	15x2	23,5
1B-419LO22Y	L	22	160	44	27,5	38,5	30x2	36	27	20x2	32,5
1B-419LO22Y	L	28	160	47	30,5	41,5	36x2	41	36	26x2	52,5
1B-419LO35Y	L	35	160	56	34,5	51	45x2	50	41	32x2,5	69
1B-419LO42Y	L	42	160	63	40	56	52x2	60	50	38x2,5	105
1B-419SO06Y	S	6	630	31	16	27	14x1,5	17	12	4x1,5	6,2
1B-419SO08Y	S	8	630	32	17	27,5	16x1,5	19	14	6x1,5	7,5
1B-419SO10Y	S	10	630	34	17,5	30	18x1,5	22	17	7,5x1,5	11,3

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	L1 mm	L2 mm	Ø F1 mm	CH1 mm	CH2 mm	O-Ring mm	Waga 100 szt. kg
1B-419SO12Y	S	12	630	38	21,5	31	20x1,5	24	17	9x1,5	14
1B-419SO14Y	S	14	630	40	22	35	22x1,5	27	19	10x2	19,5
1B-419SO16Y	S	16	400	43	24,5	36,5	24x1,5	30	24	12x2	26
1B-419SO20Y	S	20	400	48	26,5	44,5	30x2	36	27	16,3x2,4	40,5
1B-419SO25Y	S	25	400	54	30	50	36x2	46	36	20,3x2,4	75
1B-419SO30Y	S	30	400	62	35,5	55	42x2	50	41	25,3x2,4	96,5
1B-419SO38Y	S	38	315	72	41	63	52x2	60	50	33,3x2,4	142,5