



Przyłącze Proste Z Uszczelnieniem Typ: Ba. 19

Liczba wariantów: **45**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA190402	6	1/4'	7/16'	1/8'	28,7	14	6,3	16	350
OO-BA190404	6	1/4'	7/16'	1/4'	32	14	9,5	19	350
OO-BA190406	6	1/4'	7/16'	3/8'	33	14	9,5	22	350
OO-BA190408	6	1/4'	7/16'	1/2'	38,6	14	13	30	350
OO-BA190502	8	5/16'	1/2'	1/8'	28,7	14	6,3	16	350
OO-BA190504	8	5/16'	1/2'	1/4'	32	14	9,5	19	350
OO-BA190506	8	5/16'	1/2'	3/8'	33,7	14	9,5	22	350
OO-BA190602	10	3/8'	9/16'	1/8'	28,7	14,1	6,3	16	350
OO-BA190604	10	3/8'	9/16'	1/4'	32	14,1	9,5	19	350
OO-BA190606	10	3/8'	9/16'	3/8'	33	14,1	9,5	22	350
OO-BA190608	10	3/8'	9/16'	1/2'	38,6	14,1	13	30	350
OO-BA190804	12	1/2'	3/4'	1/4'	35	16,7	9,5	19	350
OO-BA190806	12	1/2'	3/4'	3/8'	36	16,7	9,5	22	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA190808	12	1/2'	3/4'	1/2'	41,4	16,7	13	30	350
OO-BA190812	12	1/2'	3/4'	3/4'	42,4	16,7	13	36	250
OO-BA191006	14	-	7/8'	3/8'	39,1	19,3	9,5	24	350
OO-BA191006	15	-	7/8'	3/8'	39,1	19,3	9,5	24	350
OO-BA191006	16	5/8'	7/8'	3/8'	39,1	19,3	9,5	24	350
OO-BA191008	14	-	7/8'	1/2'	43,9	19,3	13	30	350
OO-BA191008	15	-	7/8'	1/2'	43,9	19,3	13	30	350
OO-BA191008	16	5/8'	7/8'	1/2'	43,9	19,3	13	30	350
OO-BA191012	14	-	7/8'	3/4'	43,9	19,3	13	36	250
OO-BA191012	15	-	7/8'	3/4'	43,9	19,3	13	36	250
OO-BA191012	16	5/8'	7/8'	3/4'	43,9	19,3	13	36	250
OO-BA191206	18	-	1 1/16'	3/8'	42,4	21,9	9,5	30	350
OO-BA191206	20	3/4'	1 1/16'	3/8'	42,4	21,9	9,5	30	350
OO-BA191208	18	-	1 1/16'	1/2'	46,7	21,9	13	30	350
OO-BA191208	20	3/4'	1 1/16'	1/2'	46,7	21,9	13	30	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA191212	18	-	11/16'	3/4'	47,5	21,9	13	36	250
OO-BA191212	20	3/4'	11/16'	3/4'	47,5	21,9	13	36	250
OO-BA191216	18	-	11/16'	1'	52,6	21,9	16	46	250
OO-BA191216	20	3/4'	11/16'	1'	52,6	21,9	16	46	250
OO-BA191612	25	1'	15/16'	3/4'	48,5	23,1	13	36	250
OO-BA191616	25	1'	15/16'	1'	53,6	23,1	16	46	250
OO-BA191620	25	1'	15/16'	1 1/4'	55,1	23,1	16	50	175
OO-BA191624	25	1'	15/16'	1 1/2'	55,7	23,1	16	60	175
OO-BA192016	30	-	15/8'	1'	53,6	24,3	16	46	210
OO-BA192016	32	1 1/4'	15/8'	1'	53,6	24,3	16	46	210
OO-BA192020	30	-	15/8'	1 1/4'	56,9	24,3	16	50	175
OO-BA192020	32	1 1/4'	15/8'	1 1/4'	56,9	24,3	16	50	175
OO-BA192024	30	-	15/8'	1 1/2'	56,8	24,3	16	60	140
OO-BA192024	32	1 1/4'	15/8'	1 1/2'	56,8	24,3	16	60	140
OO-BA192416	38	1 1/2'	17/8'	1'	57,5	27,5	16	50	140

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA192420	38	1 1/2'	1 7/8'	1 1/4'	60,4	27,5	16	50	140
OO-BA192424	38	1 1/2'	1 7/8'	1 1/2'	61	27,5	16	60	140