



Przyłącze Proste Z Uszczelnieniem Typ: Ba. 20

Liczba wariantów: 45



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA200402	6	1/4'	7/16'	1/8'	30	14	8	14	350
OO-BA200404	6	1/4'	7/16'	1/4'	35	14	12	19	350
OO-BA200406	6	1/4'	7/16'	3/8'	35,5	14	12	22	350
OO-BA200408	6	1/4'	7/16'	1/2'	39	14	14	27	350
OO-BA200502	8	5/16'	1/2'	1/8'	30	14	8	14	350
OO-BA200504	8	5/16'	1/2'	1/4'	35	14	12	19	350
OO-BA200506	8	5/16'	1/2'	3/8'	35,7	14	12	22	350
OO-BA200602	10	3/8'	9/16'	1/8'	31	14,1	8	16	350
OO-BA200604	10	3/8'	9/16'	1/4'	35	14,1	12	19	350
OO-BA200606	10	3/8'	9/16'	3/8'	36	14,1	12	22	350
OO-BA200608	10	3/8'	9/16'	1/2'	39,5	14,1	14	27	350
OO-BA200804	12	1/2'	3/4'	1/4'	38,5	16,7	12	19	350
OO-BA200806	12	1/2'	3/4'	3/8'	39	16,7	12	22	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA200808	12	1/2'	3/4'	1/2'	42	16,7	14	27	350
OO-BA200812	12	1/2'	3/4'	3/4'	45,5	16,7	16	32	250
OO-BA201006	14	-	7/8'	3/8'	42,5	19,3	12	24	350
OO-BA201006	15	-	7/8'	3/8'	42,5	19,3	12	24	350
OO-BA201006	16	5/8'	7/8'	3/8'	42,5	19,3	12	24	350
OO-BA201008	14	-	7/8'	1/2'	44,5	19,3	14	27	350
OO-BA201008	15	-	7/8'	1/2'	44,5	19,3	14	27	350
OO-BA201008	16	5/8'	7/8'	1/2'	44,5	19,3	14	27	350
OO-BA201012	14	-	7/8'	3/4'	48	19,3	16	32	250
OO-BA201012	15	-	7/8'	3/4'	48	19,3	16	32	250
OO-BA201012	16	5/8'	7/8'	3/4'	48	19,3	16	32	250
OO-BA201206	18	-	11/16'	3/8'	45,5	21,9	12	27	350
OO-BA201206	20	3/4'	11/16'	3/8'	45,5	21,9	12	27	350
OO-BA201208	18	-	11/16'	1/2'	49	21,9	14	27	350
OO-BA201208	20	3/4'	11/16'	1/2'	49	21,9	14	27	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA201212	18	-	11/16'	3/4'	51	21,9	16	32	250
OO-BA201212	20	3/4'	11/16'	3/4'	51	21,9	16	32	250
OO-BA201216	18	-	11/16'	1'	53,5	21,9	18	41	250
OO-BA201216	20	3/4'	11/16'	1'	53,5	21,9	18	41	250
OO-BA201612	25	1'	15/16'	3/4'	52,5	23,1	16	36	250
OO-BA201616	25	1'	15/16'	1'	54,5	23,1	18	41	250
OO-BA201620	25	1'	15/16'	1 1/4'	58,5	23,1	20	50	175
OO-BA201624	25	1'	15/16'	1 1/2'	62	23,1	22	55	175
OO-BA202016	30	-	15/8'	1'	56	24,3	18	46	210
OO-BA202016	32	1 1/4'	15/8'	1'	56	24,3	18	46	210
OO-BA202020	30	-	15/8'	1 1/4'	60	24,3	20	50	175
OO-BA202020	32	1 1/4'	15/8'	1 1/4'	60	24,3	20	50	175
OO-BA202024	30	-	15/8'	1 1/2'	63,8	24,3	22	55	140
OO-BA202024	32	1 1/4'	15/8'	1 1/2'	63,8	24,3	22	55	140
OO-BA202416	38	1 1/2'	17/8'	1'	60	27,5	18	50	140

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA202420	38	1 1/2'	1 7/8'	1 1/4'	65	27,5	20	50	140
OO-BA202424	38	1 1/2'	1 7/8'	1 1/2'	67	27,5	22	55	140