


Przyłącze Proste Z Uszczelnieniem Typ: Ba. 21

Liczba wariantów: **44**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA210404	6	1/4'	7/16'	7/16'	31,2	14	9,1	14	350
OO-BA210405	6	1/4'	7/16'	1/2'	31,2	14	9,1	16	350
OO-BA210408	6	1/4'	7/16'	3/4'	35	14	11,1	22	350
OO-BA210505	8	5/16'	1/2'	1/2'	31,2	14	9,1	16	350
OO-BA210506	8	5/16'	1/2'	9/16'	33	14	9,9	17	350
OO-BA210604	10	3/8'	9/16'	7/16'	32,2	14,1	9,1	16	350
OO-BA210605	10	3/8'	9/16'	1/2'	32,2	14,1	9,1	16	350
OO-BA210605	10	3/8'	9/16'	9/16'	33	14,1	9,9	17	350
OO-BA210608	10	3/8'	9/16'	3/4'	35,1	14,1	11,1	22	350
OO-BA210610	10	3/8'	9/16'	7/8'	35	14,1	12,7	27	350
OO-BA210806	12	1/2'	3/4'	9/16'	36,6	16,7	9,9	19	350
OO-BA210808	12	1/2'	3/4'	3/4'	37,6	16,7	11,1	22	350
OO-BA210810	12	1/2'	3/4'	7/8'	40,6	16,7	12,7	27	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA210812	12	1/2'	3/4'	1 1/16'	44,7	16,7	15,1	32	350
OO-BA211008	14	-	7/8'	3/4'	40,6	19,3	11,1	24	350
OO-BA211008	15	-	7/8'	3/4'	40,6	19,3	11,1	24	350
OO-BA211008	16	5/8'	7/8'	3/4'	40,6	19,3	11,1	24	350
OO-BA211010	14	-	7/8'	7/8'	43,2	19,3	12,7	27	350
OO-BA211010	15	-	7/8'	7/8'	43,2	19,3	12,7	27	350
OO-BA211010	16	5/8'	7/8'	7/8'	43,2	19,3	12,7	27	350
OO-BA211012	14	-	7/8'	1 1/16'	47,2	19,3	15,1	32	350
OO-BA211012	15	-	7/8'	1 1/16'	47,2	19,3	15,1	32	350
OO-BA211012	16	5/8'	7/8'	1 1/16'	47,2	19,3	15,1	32	350
OO-BA211208	18	-	1 1/16'	3/4'	45,2	21,9	11,1	27	350
OO-BA211208	20	3/4'	1 1/16'	3/4'	45,2	21,9	11,1	27	350
OO-BA211210	18	-	1 1/16'	7/8'	46,4	21,9	12,7	27	350
OO-BA211210	20	3/4'	1 1/16'	7/8'	46,4	21,9	12,7	27	350
OO-BA211212	18	-	1 1/16'	1 1/16'	50	21,9	15,1	32	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA211212	20	3/4'	11/16'	11/16'	50	21,9	15,1	32	350
OO-BA211216	18	-	11/16'	1 5/16'	50,8	21,9	15,1	38	350
OO-BA211216	20	3/4'	11/16'	1 5/16'	50,8	21,9	15,1	38	350
OO-BA211610	25	1'	1 5/16'	7/8'	52,8	23,1	12,7	38	280
OO-BA211612	25	1'	1 5/16'	11/16'	51,1	23,1	15,1	36	280
OO-BA211616	25	1'	1 5/16'	1 5/16'	51,8	23,1	15,1	38	280
OO-BA211620	25	1'	1 5/16'	1 5/8'	53,8	23,1	15,1	50	280
OO-BA212016	30	-	1 5/8'	1 5/16'	55,1	24,3	15,1	50	210
OO-BA212016	32	1 1/4'	1 5/8'	1 5/16'	55,1	24,3	15,1	50	210
OO-BA212020	30	-	1 5/8'	1 5/8'	55,1	24,3	15,1	50	210
OO-BA212020	32	1 1/4'	1 5/8'	1 5/8'	55,1	24,3	15,1	50	210
OO-BA212024	30	-	1 5/8'	1 7/8'	56	24,3	15,1	55	140
OO-BA212024	32	1 1/4'	1 5/8'	1 7/8'	56	24,3	15,1	55	140
OO-BA212420	38	1 1/2'	1 7/8'	1 5/8'	55,5	27,5	15,1	55	140
OO-BA212424	38	1 1/2'	1 7/8'	1 7/8'	60,2	27,5	15,1	55	140

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OO-BA21O406	6	1/4'	7/16'	9/16'	33	14	9,9	17	350