


Przyłącze Proste Z Uszczelnieniem Typ: Ba. 23 W

Liczba wariantów: **28**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 metryczne mm	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
BA.23.04.02W	6	1/4'	7/16'	10x1	31	14	7,5	16	350
BA.23.05.03W	8	5/16'	1/2'	12x1,5	33,5	14	9,5	19	350
BA.23.06.04W	10	3/8'	9/16'	14x1,5	33,5	14,1	9,5	19	350
BA.23.06.05W	10	3/8'	9/16'	16x1,5	35	14,1	10	22	350
BA.23.08.04W	12	1/2'	3/4'	14x1,5	36	16,7	9,5	19	350
BA.23.08.05W	12	1/2'	3/4'	16x1,5	37,5	16,7	10	22	350
BA.23.08.06W	12	1/2'	3/4'	18x1,5	39	16,7	11	24	350
BA.23.08.08W	12	1/2'	3/4'	22x1,5	39	16,7	11,5	27	350
BA.23.10.04W	14	-	7/8'	14x1,5	40	19,3	9,5	24	350
BA.23.10.04W	15	-	7/8'	14x1,5	40	19,3	9,5	24	350
BA.23.10.04W	16	5/8'	7/8'	14x1,5	40	19,3	9,5	24	350
BA.23.10.06W	14	-	7/8'	18x1,5	42	19,3	11	24	350
BA.23.10.06W	15	-	7/8'	18x1,5	42	19,3	11	24	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 metryczne mm	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
BA.23.10.06W	16	5/8'	7/8'	18x1,5	42	19,3	11	24	350
BA.23.10.08W	14	-	7/8'	22x1,5	43	19,3	11,5	27	350
BA.23.10.08W	15	-	7/8'	22x1,5	43	19,3	11,5	27	350
BA.23.10.08W	16	5/8'	7/8'	22x1,5	43	19,3	11,5	27	350
BA.23.12.06W	18	-	1 1/16'	18x1,5	44	21,9	11	27	350
BA.23.12.06W	20	3/4'	1 1/16'	18x1,5	44	21,9	11	27	350
BA.23.12.08W	18	-	1 1/16'	22x1,5	45,5	21,9	11,5	27	350
BA.23.12.08W	20	3/4'	1 1/16'	22x1,5	45,5	21,9	11,5	27	350
BA.23.12.14W	18	-	1 1/16'	27x2	49	21,9	14	32	350
BA.23.12.14W	20	3/4'	1 1/16'	27x2	49	21,9	14	32	350
BA.23.16.14W	25	1'	1 5/16'	27x2	50,5	23,1	14	36	250
BA.23.16.16W	25	1'	1 5/16'	33x2	51,5	23,1	14	41	250
BA.23.20.20W	30	-	1 5/8'	42x2	55	24,3	14	50	210
BA.23.20.20W	32	1 1/4'	1 5/8'	42x2	55	24,3	14	50	210
BA.23.24.24W	38	1 1/2'	1 7/8'	48x2	59,5	27,5	15,5	55	140

