



Przyłącze Proste Typ: Ba. 26

Liczba wariantów: **34**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPT cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OBA260402	6	1/4'	7/16'	1/8'	30,7	14	9,7	13	350
OBA260404	6	1/4'	7/16'	1/4'	35,3	14	14,2	14	350
OBA260502	8	5/16'	1/2'	1/8'	30,7	14	9,7	14	350
OBA260504	8	5/16'	1/2'	1/4'	35,3	14	14,2	14	350
OBA260604	10	3/8'	9/16'	1/4'	35,6	14,1	14,2	16	350
OBA260606	10	3/8'	9/16'	3/8'	35,6	14,1	14,2	19	350
OBA260608	10	3/8'	9/16'	1/2'	41,1	14,1	19	22	350
OBA260804	12	1/2'	3/4'	1/4'	38,1	16,7	14,2	19	350
OBA260806	12	1/2'	3/4'	3/8'	38,1	16,7	14,2	19	350
OBA260808	12	1/2'	3/4'	1/2'	43,7	16,7	19	22	350
OBA261006	14	-	7/8'	3/8'	41,9	19,3	14,2	24	350
OBA261006	15	-	7/8'	3/8'	41,9	19,3	14,2	24	350
OBA261006	16	5/8'	7/8'	3/8'	41,9	19,3	14,2	24	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPT cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OBA261008	14	-	7/8'	1/2'	46,7	19,3	19	24	350
OBA261008	15	-	7/8'	1/2'	46,7	19,3	19	24	350
OBA261008	16	5/8'	7/8'	1/2'	46,7	19,3	19	24	350
OBA261012	14	-	7/8'	3/4'	48,3	19,3	19	27	350
OBA261012	15	-	7/8'	3/4'	48,3	19,3	19	27	350
OBA261012	16	5/8'	7/8'	3/4'	48,3	19,3	19	27	350
OBA261208	18	-	11/16'	1/2'	50,8	21,9	19	27	350
OBA261208	20	3/4'	11/16'	1/2'	50,8	21,9	19	27	350
OBA261212	18	-	11/16'	3/4'	50,8	21,9	19	27	350
OBA261212	20	3/4'	11/16'	3/4'	50,8	21,9	19	27	350
OBA261216	18	-	11/16'	1'	56,6	21,9	23,9	36	280
OBA261216	20	3/4'	11/16'	1'	56,6	21,9	23,9	36	280
OBA261608	25	1'	15/16'	1/2'	53,1	23,1	19	36	280
OBA261612	25	1'	15/16'	3/4'	53,1	23,1	19	36	280
OBA261616	25	1'	15/16'	1'	57,9	23,1	23,9	36	280

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPT cal	B mm	C mm	C2 mm	CH mm	Ciśnienie pracy bar
OBA262016	30	-	1 5/8'	1'	60,2	24,3	23,9	46	210
OBA262016	32	1 1/4'	1 5/8'	1'	60,2	24,3	23,9	46	210
OBA262020	30	-	1 5/8'	1 1/4'	61	24,3	24,6	46	210
OBA262020	32	1 1/4'	1 5/8'	1 1/4'	61	24,3	24,6	46	210
OBA262420	38	1 1/2'	1 7/8'	1 1/4'	65,5	27,5	24,6	50	140
OBA262424	38	1 1/2'	1 7/8'	1 1/2'	66,3	27,5	25,4	50	140