



Złącze Typ: Ba. 31

Liczba wariantów: **27**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R mm	Ø R cal	Ø R cal	Ø R2- UNF JIC 37° cal	Ø R- UNF JIC 37° cal	B mm	CH mm	Typ	C mm	Ciśnienie pracy bar
OBA310504	8	6	3/8'	5/16'	1/2'	7/16'	28	19	A	14	350
OBA310604	10	6	3/8'	1/4'	9/16'	7/16'	24,6	-	B	14	350
OBA310605	10	8	3/8'	5/16'	9/16'	1/2'	29	19	A	14	350
OBA310804	12	6	1/2'	1/4'	3/4'	7/16'	25,4	-	B	14	350
OBA310805	12	8	1/2'	5/16'	3/4'	1/2'	25,4	-	B	14	350
OBA310806	12	10	1/2'	3/8'	3/4'	9/16'	25,4	-	B	14,1	350
OBA311008	14	12	-	-	7/8'	3/4'	36,5	27	A	16,7	350
OBA311008	15	12	-	-	7/8'	3/4'	36,5	27	A	16,7	350
OBA311008	16	12	5/8'	1/2'	7/8'	3/4'	36,5	27	A	16,7	350
OBA311206	18	10	-	-	1 1/16'	9/16'	27,7	-	B	14,1	350
OBA311206	20	10	3/4'	3/8'	1 1/16'	9/16'	27,7	-	B	14,1	350
OBA311210	18	14	-	-	1 1/16'	7/8'	42,1	32	A	19,3	350
OBA311210	18	15	-	-	1 1/16'	7/8'	42,1	32	A	19,3	350

Nr katalogowy	Ø R mm	Ø R mm	Ø R cal	Ø R cal	Ø R2-UNF JIC 37° cal	Ø R-UNF JIC 37° cal	B mm	CH mm	Typ	C mm	Ciśnienie pracy bar
OBA311210	18	16	-	-	1 1/16'	7/8'	42,1	32	A	19,3	350
OBA311210	20	14	-	-	1 1/16'	7/8'	42,1	32	A	19,3	350
OBA311210	20	15	-	-	1 1/16'	7/8'	42,1	32	A	19,3	350
OBA311210	20	16	3/4'	5/8'	1 1/16'	7/8'	42,1	32	A	19,3	350
OBA311612	25	18	-	-	1 5/16'	1 1/16'	37,3	-	B	21,9	280
OBA311612	25	20	1'	3/4'	1 5/16'	1 1/16'	37,3	-	B	21,9	280
OBA312012	30	18	-	-	1 5/8'	1 1/16'	38,8	-	B	21,9	210
OBA312012	30	20	-	-	1 5/8'	1 1/16'	38,8	-	B	21,9	210
OBA312012	32	18	-	-	1 5/8'	1 1/16'	38,8	-	B	21,9	210
OBA312012	32	20	1 1/4'	3/4'	1 5/8'	1 1/16'	38,8	-	B	21,9	210
OBA312016	30	25	-	-	1 5/8'	1 5/16'	40,3	-	B	23,1	210
OBA312016	32	25	1 1/4'	1'	1 5/8'	1 5/16'	40,3	-	B	23,1	210
OBA312420	38	30	-	-	1 7/8'	1 5/8'	42,9	-	B	24,3	140
OBA312420	38	32	1 1/2'	1 1/4'	1 7/8'	1 5/8'	42,9	-	B	24,3	140