


Złącze Typ: Ba. 47

Liczba wariantów: 14



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPT cal	B mm	C1 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
BA.47.04.02	6	1/4'	7/16'	1/8'	33,9	15,5	9,7	13	17	350
BA.47.04.04	6	1/4'	7/16'	1/4'	38,5	15,6	14,2	14	17	350
BA.47.05.04	8	5/16'	1/2'	1/4'	41,3	17,6	14,2	14	19	350
BA.47.06.04	10	3/8'	9/16'	1/4'	41,5	17,8	14,2	14	19	350
BA.47.06.06	10	3/8'	9/16'	3/8'	41,5	17,8	14,2	19	19	350
BA.47.08.04	12	1/2'	3/4'	1/4'	44,6	19,7	14,2	19	24	350
BA.47.08.06	12	1/2'	3/4'	3/8'	44,6	19,7	14,2	19	24	350
BA.47.10.06	14-15-16	5/8'	7/8'	3/8'	47,3	20,4	14,2	22	27	350
BA.47.10.08	14-15-16	5/8'	7/8'	1/2'	52,1	20,4	19	22	27	350
BA.47.12.08	18-20	3/4'	1 1/16'	1/2'	56,7	23,4	19	27	32	350
BA.47.12.12	18-20	3/4'	1 1/16'	3/4'	56,7	23,4	19	27	32	350
BA.47.16.12	25	1'	1 5/16'	3/4'	59,6	25,5	19	32	38	280
BA.47.16.16	25	1'	1 5/16'	1'	64,4	25,4	23,9	36	38	280

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPT cal	B mm	C1 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
BA.47.20.20	30-32	1 1/4'	1 5/8'	1 1/4'	69,6	29,1	24,6	46	50	210