




Złącze Typ: Ba. 49

Liczba wariantów: 19



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C1 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-BA490402	6	1/4'	7/16'	1/8'	31,4	16,4	6,3	16	17	350
OO-BA490404	6	1/4'	7/16'	1/4'	34,6	16,4	9,5	19	17	350
OO-BA490502	8	5/16'	1/2'	1/8'	33,6	17,8	6,3	16	19	350
OO-BA490504	8	5/16'	1/2'	1/4'	37,5	18,5	9,5	19	19	350
OO-BA490604	10	3/8'	9/16'	1/4'	38	19	9,5	19	19	350
OO-BA490606	10	3/8'	9/16'	3/8'	39	20	9,5	22	19	350
OO-BA490804	12	1/2'	3/4'	1/4'	41,2	21	9,5	19	24	350
OO-BA490806	12	1/2'	3/4'	3/8'	41,7	21,5	9,5	22	24	350
OO-BA490808	12	1/2'	3/4'	1/2'	46,2	22,5	13	27	24	350
OO-BA491006	14-15-16	5/8'	7/8'	3/8'	44,2	22	9,5	22	27	350
OO-BA491008	14-15-16	5/8'	7/8'	1/2'	47,9	22,2	13	30	27	350
OO-BA491208	18-20	3/4'	1 1/16'	1/2'	50,3	23	13	30	32	350
OO-BA491212	18-20	3/4'	1 1/16'	3/4'	50,3	23	13	36	32	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C1 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-BA491612	25	1'	15/16'	3/4'	55,6	27,5	13	36	38	280
OO-BA491616	25	1'	15/16'	1'	58,6	27,5	16	46	38	280
OO-BA492016	30-32	1 1/4'	15/8'	1'	61,9	30	16	46	50	210
OO-BA492020	30-32	1 1/4'	15/8'	1 1/4'	64,9	33	16	50	50	175
OO-BA492420	38	1 1/2'	17/8'	1 1/4'	70,1	35,5	16	50	60	140
OO-BA492424	38	1 1/2'	17/8'	1 1/2'	70,1	35,5	16	60	60	140