



Złącze Typ: Ba. 58

Liczba wariantów: 18



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C1 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-BA580402	6	1/4'	7/16'	1/8'	32,9	16,2	8	14	17	350
OO-BA580404	6	1/4'	7/16'	1/4'	37,1	16,4	12	19	17	350
OO-BA580502	8	5/16'	1/2'	1/8'	35,5	18	8	14	19	350
OO-BA580504	8	5/16'	1/2'	1/4'	40	18,5	12	19	19	350
OO-BA580604	10	3/8'	9/16'	1/4'	40,5	19	12	19	19	350
OO-BA580606	10	3/8'	9/16'	3/8'	42	20,5	12	22	19	350
OO-BA580804	12	1/2'	3/4'	1/4'	44,2	21,5	12	19	24	350
OO-BA580806	12	1/2'	3/4'	3/8'	44,7	22	12	22	24	350
OO-BA581006	14-15-16	5/8'	7/8'	3/8'	47,4	22,7	12	24	27	350
OO-BA581008	14-15-16	5/8'	7/8'	1/2'	49,9	23,2	14	27	27	350
OO-BA581208	18-20	3/4'	1 1/16'	1/2'	52,3	24	14	27	32	350
OO-BA581212	18-20	3/4'	1 1/16'	3/4'	54,3	24	16	32	32	350
OO-BA581612	25	1'	1 5/16'	3/4'	59,6	28,5	16	32	38	280

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	C1 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-BA581616	25	1'	15/16'	1'	61,6	28,5	18	41	38	280
OO-BA582016	30-32	1 1/4'	15/16'	1'	67,4	33,5	18	41	50	210
OO-BA582020	30-32	1 1/4'	15/8'	1 1/4'	69,4	33,5	20	50	50	210
OO-BA582420	38	1 1/2'	17/8'	1 1/4'	74,6	36	20	50	60	140
OO-BA582424	38	1 1/2'	17/8'	1 1/2'	76,6	36	22	55	60	140