



Złącze Typ: Ba. 62

Liczba wariantów: 11



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	C2 mm	E mm	CH mm	Ciśnienie pracy bar
OO-BA620404	6	1/4'	7/16'	7/16'	52,8	9,1	35,3	14	350
OO-BA620606	10	3/8'	9/16'	9/16'	58,7	9,9	39,6	17	350
OO-BA620808	12	1/2'	3/4'	3/4'	68,6	11,1	47,8	22	350
OO-BA621010	14	-	7/8'	7/8'	77,2	12,7	53,1	27	350
OO-BA621010	15	-	7/8'	7/8'	77,2	12,7	53,1	27	350
OO-BA621010	16	5/8'	7/8'	7/8'	77,2	12,7	53,1	27	350
OO-BA621212	18	-	1 1/16'	1 1/16'	91,7	15,1	63,5	32	350
OO-BA621212	20	3/4'	1 1/16'	1 1/16'	91,7	15,1	63,5	32	350
OO-BA621616	25	1'	1 5/16'	1 5/16'	101	15,1	72,1	38	280
OO-BA622020	30	-	1 5/8'	1 5/8'	119,1	15,1	88,1	50	210
OO-BA622020	32	1 1/4'	1 5/8'	1 5/8'	119,1	15,1	88,1	50	210