



Przyłącze Kątowe Typ: St. 05

Liczba wariantów: 35



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST050402	6	1/4'	7/16'	1/8'	22,6	26	6,3	11	14	350
OO-ST050404	6	1/4'	7/16'	1/4'	26,9	32	9,5	14	19	350
OO-ST050502	8	5/16'	1/2'	1/8'	24,1	27	6,3	13	14	350
OO-ST050504	8	5/16'	1/2'	1/4'	26,9	32	9,5	14	19	350
OO-ST050506	8	5/16'	1/2'	3/8'	29	37	9,5	19	22	350
OO-ST050604	10	3/8'	9/16'	1/4'	26,9	32	9,5	14	19	350
OO-ST050606	10	3/8'	9/16'	3/8'	29	37	9,5	19	22	350
OO-ST050608	10	3/8'	9/16'	1/2'	31,1	43	13	22	27	350
OO-ST050804	12	1/2'	3/4'	1/4'	31,8	37	9,5	19	19	350
OO-ST050806	12	1/2'	3/4'	3/8'	31,8	37	9,5	19	22	350
OO-ST050808	12	1/2'	3/4'	1/2'	33,7	43	13	22	27	350
OO-ST051006	14	-	7/8'	3/8'	36,8	43	9,5	22	22	350
OO-ST051006	15	-	7/8'	3/8'	36,8	43	9,5	22	22	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST051006	16	5/8'	7/8'	3/8'	36,8	43	9,5	22	22	350
OO-ST051008	14	-	7/8'	1/2'	36,8	43	13	22	27	250
OO-ST051008	15	-	7/8'	1/2'	36,8	43	13	22	27	350
OO-ST051008	16	5/8'	7/8'	1/2'	36,8	43	13	22	27	350
OO-ST051012	14	-	7/8'	3/4'	38,9	49,5	13	27	36	250
OO-ST051012	15	-	7/8'	3/4'	38,9	49,5	13	27	36	250
OO-ST051012	16	5/8'	7/8'	3/4'	38,9	49,5	13	27	36	250
OO-ST051208	18	-	1 1/16'	1/2'	42,2	49,5	13	27	27	350
OO-ST051208	20	3/4'	1 1/16'	1/2'	42,2	49,5	13	27	27	350
OO-ST051212	18	-	1 1/16'	3/4'	42,2	49,5	13	27	36	250
OO-ST051212	20	3/4'	1 1/16'	3/4'	42,2	49,5	13	27	36	250
OO-ST051216	18	-	1 1/16'	1'	44,8	52	16	33	41	250
OO-ST051216	20	3/4'	1 1/16'	1'	44,8	52	16	33	41	250
OO-ST051612	25	1'	1 5/16'	3/4'	46	52	16	33	36	250
OO-ST051616	25	1'	1 5/16'	1'	46	52	16	33	41	250

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
00-ST051620	25	1"	1 5/16"	1 1/4"	51	57	16	41	50	175
00-ST052016	30	-	1 5/8"	1"	52,3	57	16	41	41	210
00-ST052016	32	1 1/4"	1 5/8"	1"	52,3	57	16	41	41	210
00-ST052020	30	-	1 5/8"	1 1/4"	52,3	57	16	41	50	175
00-ST052020	32	1 1/4"	1 5/8"	1 1/4"	52,3	57	16	41	50	175
00-ST052420	38	1 1/2"	1 7/8"	1 1/4"	59,2	60,5	16	48	50	140
00-ST052424	38	1 1/2"	1 7/8"	1 1/2"	59,2	60,5	16	48	55	140