



Przyłącze Kątowe Typ: St. 07W

Liczba wariantów: 20



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 metryczne cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
ST.07.04.02W	6	1/4'	7/16'	10x1	22,6	27	7,5	11	14	350
ST.07.05.03W	8	5/16'	1/2'	12x1,5	24,1	29	9,5	13	17	350
ST.07.06.04W	10	3/8'	9/16'	14x1,5	26,9	34	9,5	14	19	350
ST.07.08.05W	12	1/2'	3/4'	16x1,5	31,8	36	10	19	22	350
ST.07.08.06W	12	1/2'	3/4'	18x1,5	31,8	38	11	19	24	350
ST.07.10.06W	14	-	7/8'	18x1,5	36,8	41,5	11	22	24	350
ST.07.10.06W	15	-	7/8'	18x1,5	36,8	41,5	11	22	24	350
ST.07.10.06W	16	5/8'	7/8'	18x1,5	36,8	41,5	11	22	24	350
ST.07.10.08W	14	-	7/8'	22x1,5	36,8	42,5	11	22	27	350
ST.07.10.08W	15	-	7/8'	22x1,5	36,8	42,5	11	22	27	350
ST.07.10.08W	16	5/8'	7/8'	22x1,5	36,8	42,5	11	22	27	350
ST.07.12.08W	18	-	1 1/16'	22x1,5	42,2	45	11	27	27	350
ST.07.12.08W	20	3/4'	1 1/16'	22x1,5	42,2	45	11	27	27	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 metryczne cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
ST.07.12.14W	18	-	11/16'	27x2	42,2	51	13,5	27	32	350
ST.07.12.14W	20	3/4'	11/16'	27x2	42,2	51	13,5	27	32	350
ST.07.16.14W	25	1'	15/16'	27x2	46	53	13,5	33	32	250
ST.07.16.16W	25	1'	15/16'	33x2	46	53	13,5	33	41	250
ST.07.20.20W	30	-	15/8'	42x2	52,3	58	13,5	41	50	210
ST.07.20.20W	32	1 1/4'	15/8'	42x2	52,3	58	13,5	41	50	210
ST.07.24.24W	38	1 1/2'	17/8'	48x2	59,2	63,5	17	48	55	140