




Przyłącze Kątowe Typ: St. 12

Liczba wariantów: **32**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2-BSPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
OSTI20402	6	1/4'	7/16'	1/8'	22,6	19,8	11	350
OSTI20404	6	1/4'	7/16'	1/4'	26,9	27,7	14	350
OSTI20502	8	5/16'	1/2'	1/8'	24,1	19,8	13	350
OSTI20504	8	5/16'	1/2'	1/4'	26,9	27,7	14	350
OSTI20604	10	3/8'	9/16'	1/4'	26,9	27,7	14	350
OSTI20606	10	3/8'	9/16'	3/8'	29	31	19	350
OSTI20608	10	3/8'	9/16'	1/2'	31,2	37,3	22	350
OSTI20804	12	1/2'	3/4'	1/4'	31,8	31	19	350
OSTI20806	12	1/2'	3/4'	3/8'	31,8	31	19	350
OSTI20808	12	1/2'	3/4'	1/2'	33,7	37,3	22	350
OSTI21006	14	-	7/8'	3/8'	36,8	33	22	350
OSTI21006	15	-	7/8'	3/8'	36,8	33	22	350
OSTI21006	16	5/8'	7/8'	3/8'	36,8	33	22	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2-BSPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
OST121008	14	-	7/8'	1/2'	36,8	37,3	22	350
OST121008	15	-	7/8'	1/2'	36,8	37,3	22	350
OST121008	16	5/8'	7/8'	1/2'	36,8	37,3	22	350
OST121012	14	-	7/8'	3/4'	38,9	40,4	27	350
OST121012	15	-	7/8'	3/4'	38,9	40,4	27	350
OST121012	16	5/8'	7/8'	3/4'	38,9	40,4	27	350
OST121208	18	-	1 1/16'	1/2'	42,2	40,4	27	350
OST121208	20	3/4'	1 1/16'	1/2'	42,2	40,4	27	350
OST121212	18	-	1 1/16'	3/4'	42,2	40,4	27	350
OST121212	20	3/4'	1 1/16'	3/4'	42,2	40,4	27	350
OST121216	18	-	1 1/16'	1'	44,7	50	33	280
OST121216	20	3/4'	1 1/16'	1'	44,7	50	33	280
OST121612	25	1'	1 5/16'	3/4'	46	45,2	33	280
OST121616	25	1'	1 5/16'	1'	46	50	33	280
OST122016	30	-	1 5/8'	1'	52,3	59,6	41	210

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2-BSPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
OST122016	32	1 1/4'	1 5/8'	1'	52,3	59,6	41	210
OST122020	30	-	1 5/8'	1 1/4'	52,3	59,6	41	210
OST122020	32	1 1/4'	1 5/8'	1 1/4'	52,3	59,6	41	210
OST122424	38	1 1/2'	1 7/8'	1 1/2'	59,2	67,1	48	140