




Przyłącze Kątowe Typ: St. 35

Liczba wariantów: 17



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST350404	6	1/4'	7/16'	1/4'	21,1	29	9,5	14	19	350
OO-ST350504	8	5/16'	1/2'	1/4'	21,1	29	9,5	14	19	350
OO-ST350604	10	3/8'	9/16'	1/4'	21,1	29	9,5	14	19	350
OO-ST350806	12	1/2'	3/4'	3/8'	24,9	33	9,5	19	22	350
OO-ST350808	12	1/2'	3/4'	1/2'	26,7	38,5	13	22	27	350
OO-ST351008	14	-	7/8'	1/2'	28,2	38,5	13	22	27	350
OO-ST350608	-	-	9/16	1/2'	-	-	-	22	27	350
OO-ST351008	16	5/8'	7/8'	1/2'	28,2	38,5	13	22	27	350
OO-ST351012	14	-	7/8'	3/4'	29,8	44	13	27	36	250
OO-ST351012	15	-	7/8'	3/4'	29,8	44	13	27	36	250
OO-ST351012	16	5/8'	7/8'	3/4'	29,8	44	13	27	36	250
OO-ST351212	18	-	11/16'	3/4'	32,5	44	13	27	36	250
OO-ST351212	20	3/4'	11/16'	3/4'	32,5	44	13	27	36	250

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST351612	25	1'	1 5/16'	3/4'	37,3	47,5	13	33	36	250
OO-ST351616	25	1'	1 5/16'	1'	37,3	47,5	16	33	41	250
OO-ST351620	30	-	1 5/16'	1 1/4'	40,4	48,5	16	41	50	175
OO-ST352020	32	1 1/4'	1 5/8'	1 1/4'	40,4	48,5	16	41	50	175