



Elbow Male Coupling 45° Metric With O-Ring Type: St. 37W

Variants: 16



SCAN ME

Product variants

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 metryczne mm	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
ST.37.05.02W	8	5/16'	1/2'	10x1	21,1	29	7,5	14	14	350
ST.37.06.04W	10	3/8'	9/16'	14x1,5	21,1	29	9,5	14	19	350
ST.37.06.06W	10	3/8'	9/16'	18x1,5	22,3	33	11	19	24	350
ST.37.08.05W	12	1/2'	3/4'	16x1,5	24,9	32	10	19	22	350
ST.37.08.06W	12	1/2'	3/4'	18x1,5	24,9	36,5	11	19	24	350
ST.37.10.06W	14	-	7/8'	18x1,5	28,2	37	11	22	24	350
ST.37.10.06W	15	-	7/8'	18x1,5	28,2	37	11	22	24	350
ST.37.10.06W	16	5/8'	7/8'	18x1,5	28,2	37	11	22	24	350
ST.37.10.08W	14	-	7/8'	22x1,5	28,2	37,5	11	22	27	350
ST.37.10.08W	15	-	7/8'	22x1,5	28,2	37,5	11	22	27	350
ST.37.10.08W	16	5/8'	7/8'	22x1,5	28,2	37,5	11	22	27	350
ST.37.12.08W	18	-	1 1/16'	22x1,5	32,5	39	11	27	27	350
ST.37.12.08W	20	3/4'	1 1/16'	22x1,5	32,5	39	11	27	27	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 metryczne mm	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
ST.37.12.14W	18	-	1 1/16'	27x2	32,5	46	13,5	27	32	350
ST.37.12.14W	20	3/4'	1 1/16'	27x2	32,5	46	13,5	27	32	350
ST.37.16.16W	25	1'	1 5/16'	33x2	37,3	45,5	13,5	33	41	250