



Przyłącze Kątowe Typ: St. 41

Liczba wariantów: 30



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 NPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
OST410404	6	1/4'	7/16'	1/4'	20,8	21,8	14	350
OST410504	8	5/16'	1/2'	1/4'	20,8	21,8	14	350
OST410602	10	3/8'	9/16'	1/8'	21,1	17	14	350
OST410604	10	3/8'	9/16'	1/4'	21,1	21,8	14	350
OST410606	10	3/8'	9/16'	3/8'	22,1	24,1	19	350
OST410608	10	3/8'	9/16'	1/2'	22,4	29,7	22	350
OST410804	12	1/2'	3/4'	1/4'	24,9	24	19	350
OST410806	12	1/2'	3/4'	3/8'	24,9	24,1	19	350
OST410808	12	1/2'	3/4'	1/2'	25,2	29,7	22	350
OST410812	12	1/2'	3/4'	3/4'	26,5	30,5	27	350
OST411006	14	-	7/8'	3/8'	28,2	25	22	350
OST411006	15	-	7/8'	3/8'	28,2	25	22	350
OST411006	16	5/8'	7/8'	3/8'	28,2	25	22	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 NPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
OST411008	14	-	7/8'	1/2'	28,2	29,7	22	350
OST411008	15	-	7/8'	1/2'	28,2	29,7	22	250
OST411008	16	5/8'	7/8'	1/2'	28,2	29,7	22	350
OST411012	14	-	7/8'	3/4'	29,5	30,5	27	350
OST411012	15	-	7/8'	3/4'	29,5	30,5	27	350
OST411012	16	5/8'	7/8'	3/4'	29,5	30,5	27	350
OST411208	18	-	1 1/16'	1/2'	32,5	30,5	27	350
OST411208	20	3/4'	1 1/16'	1/2'	32,5	30,5	27	350
OST411212	18	-	1 1/16'	3/4'	32,5	30,5	27	350
OST411212	20	3/4'	1 1/16'	3/4'	32,5	30,5	27	350
OST411612	25	1'	1 5/16'	3/4'	37,3	32,5	33	280
OST411616	25	1'	1 5/16'	1'	37,3	37,6	33	280
OST412016	30	-	1 5/8'	1'	40,4	42,4	41	210
OST412016	32	1 1/4'	1 5/8'	1'	40,4	42,4	41	210
OST412020	30	-	1 5/8'	1 1/4'	40,4	42,4	41	210

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 NPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
OST412020	32	1 1/4'	1 5/8'	1 1/4'	40,4	42,4	41	210
OST412424	38	1 1/2'	1 7/8'	1 1/2'	45,2	45	48	140