



Trójnik Typ: St. 60

Liczba wariantów: 13



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST600404	6	1/4'	7/16'	7/16'	22,6	26,2	9	11	14	350
OO-ST600505	8	5/16'	1/2'	1/2'	24,1	27,7	9	13	16	350
OO-ST600506	10	3/8'	9/16'	9/16'	26,9	31,8	10	14	17	350
OO-ST600808	12	1/2'	3/4'	3/4'	31,8	36,8	11	19	22	350
OO-ST601010	14	-	7/8'	7/8'	36,8	43,2	12,7	22	27	350
ST.60.10.10	15	-	7/8'	7/8'	36,8	43,2	12,7	22	27	350
OO-ST601010	16	5/8'	7/8'	7/8'	36,8	43,2	12,7	22	27	350
ST.60.12.12	18	-	1 1/16'	1 1/16'	42,2	49,3	15	27	32	350
OO-ST601212	20	3/4'	1 1/16'	1 1/16'	42,2	49,3	15	27	32	350
OO-ST601616	25	1'	1 5/16'	1 5/16'	46	52,1	15	33	38	280
ST.60.20.20	30	-	1 5/8'	1 5/8'	52,3	57,2	15	41	50	210
OO-ST602020	32	1 1/4'	1 5/8'	1 5/8'	52,3	57,2	15	41	50	210
OO-ST602424	38	1 1/2'	1 7/8'	1 7/8'	59,2	60,7	15	48	55	140