



Trójnik Typ: St. 62

Liczba wariantów: 16



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 metryczne mm	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST620402	6	1/4'	7/16'	10x1	22,6	27	8,5	11	14	350
OO-ST620503	8	5/16'	1/2'	12x1,5	24,1	29	11	13	17	350
OO-ST620604	10	3/8'	9/16'	14x1,5	26,9	34	11	14	19	350
OO-ST620805	12	1/2'	3/4'	16x1,5	31,8	36	11,5	19	22	350
OO-ST620806	12	1/2'	3/4'	18x1,5	31,8	38	12,5	19	24	350
OO-ST621006	14	-	7/8'	18x1,5	36,8	41,5	12,5	22	24	350
OO-ST621006	15	-	7/8'	18x1,5	36,8	41,5	12,5	22	24	350
OO-ST621006	16	5/8'	7/8'	18x1,5	36,8	41,5	12,5	22	24	350
OO-ST621008	14	-	7/8'	22x1,5	36,8	42,5	12,5	22	27	350
OO-ST621008	15	-	7/8'	22x1,5	36,8	42,5	12,5	22	27	350
OO-ST621008	16	5/8'	7/8'	22x1,5	36,8	42,5	12,5	22	27	350
OO-ST621208	18	-	1 1/16'	22x1,5	42,2	45	12,5	27	27	350
OO-ST621208	20	3/4'	1 1/16'	22x1,5	42,2	45	12,5	27	27	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 metryczne mm	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST62I2I4	18	-	1 1/16'	27x2	42,2	51	15,5	27	32	350
OO-ST62I2I4	20	-	1 1/16'	27x2	42,2	51	15,5	27	32	350
OO-ST62I6I4	25	1'	1 5/16'	27x2	46	53	15,5	33	32	280