



Trójnik Typ: St. 63

Liczba wariantów: 12



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 BSPP cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST630402	6	1/4'	7/16'	1/8'	22,6	26	6,3	11	14	350
OO-ST630502	8	5/16'	1/2'	1/8'	24,1	26	6,3	13	14	350
OO-ST630604	10	3/8'	9/16'	1/4'	26,9	32,5	9,5	14	19	350
OO-ST630806	12	1/2'	3/4'	3/8'	31,8	37,5	9,5	19	22	350
ST.63.10.08	14	-	7/8'	1/2'	36,8	43	13	22	27	350
ST.63.10.08	15	-	7/8'	1/2'	36,8	43	13	22	27	350
OO-ST631008	16	5/8'	7/8'	1/2'	36,8	43	13	22	27	350
ST.63.12.12	18	-	1 1/16'	3/4'	42,2	49,5	13	27	36	250
OO-ST631212	20	3/4'	1 1/16'	3/4'	42,2	49,5	13	27	36	250
OO-ST631616	25	1'	1 5/16'	1'	46	52	16	33	41	250
ST.63.20.20	30	-	1 5/8'	1 1/4'	52,3	57	16	41	50	175
OO-ST632020	32	1 1/4'	1 5/8'	1 1/4'	52,3	57	16	41	50	175