



Trójnik Typ: St. 64W

Liczba wariantów: 16



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R- UNF JIC 37° cal	Ø R2 metryczne mm	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST640402W	6	1/4'	7/16'	10x1	22,6	27	7,5	11	14	350
OO-ST640503W	8	5/16'	1/2'	12x1,5	24,1	29	9,5	13	17	350
OO-ST640604W	10	3/8'	9/16'	14x1,5	26,9	34	9,5	14	19	350
OO-ST640805W	12	1/2'	3/4'	16x1,5	31,8	36	10	19	22	350
OO-ST640806W	12	1/2'	3/4'	18x1,5	31,8	38	11	19	24	350
OO-ST641006W	14	-	7/8'	18x1,5	36,8	41,5	11	22	24	350
OO-ST641006W	15	-	7/8'	18x1,5	36,8	41,5	11	22	24	350
OO-ST641006W	16	5/8'	7/8'	18x1,5	36,8	41,5	11	22	24	350
OO-ST641008W	14	-	7/8'	22x1,5	36,8	42,5	11	22	27	350
OO-ST641008W	15	-	7/8'	22x1,5	36,8	42,5	11	22	27	350
OO-ST641008W	16	5/8'	7/8'	22x1,5	36,8	42,5	11	22	27	350
OO-ST641208W	18	-	1 1/16'	22x1,5	42,2	45	11	27	27	350
OO-ST641208W	20	3/4'	1 1/16'	22x1,5	42,2	45	11	27	27	350

Nr katalogowy	Ø R mm	Ø R cal	Ø R- UNF JIC 37° cal	Ø R2 metryczne mm	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST64I2I4W	18	-	11/16'	27x2	42,2	51	13,5	27	32	350
OO-ST64I2I4W	20	3/4'	11/16'	27x2	42,2	51	13,5	27	32	350
OO-ST64I6I4W	25	1'	1 5/16'	27x2	46	53	13,5	33	32	250