



Trójnik Typ: St. 65

Liczba wariantów: 13



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST650404	6	1/4'	7/16'	7/16'	22,6	26,2	9	11	14	350
OO-ST650505	8	5/16'	1/2'	1/2'	24,1	27,7	9	13	16	350
OO-ST650606	10	3/8'	9/16'	9/16'	26,9	31,8	10	14	17	350
OO-ST650808	12	1/2'	3/4'	3/4'	31,8	36,8	11	19	22	350
OO-ST651010	14	-	7/8'	7/8'	36,8	43,2	12,7	22	27	350
OO-ST651010	15	-	7/8'	7/8'	36,8	43,2	12,7	22	27	350
OO-ST651010	16	5/8'	7/8'	7/8'	36,8	43,2	12,7	22	27	350
OO-ST651212	18	-	1 1/16'	1 1/16'	42,2	49,3	15	27	32	350
OO-ST651616	20	3/4'	1 1/16'	1 1/16'	42,2	49,3	15	27	32	350
OO-ST651616	25	1'	1 5/16'	1 5/16'	46	52,1	15	33	38	280
OO-ST652020	30	-	1 5/8'	1 5/8'	52,3	57,2	15	41	50	210
OO-ST652020	32	1 1/4'	1 5/8'	1 5/8'	52,3	57,2	15	41	50	210
OO-ST652424	38	1 1/2'	1 7/8'	1 7/8'	59,2	60,7	15	48	55	140