



Trójnik Typ: St. 68

Liczba wariantów: 16



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 NPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
OST680402	6	1/4'	7/16'	1/8'	22,6	19,8	11	350
OST680404	6	1/4'	7/16'	1/4'	26,9	27,7	14	350
OST680502	8	5/16'	1/2'	1/8'	24,1	19,8	13	350
OST680604	10	3/8'	9/16'	1/4'	26,9	27,7	14	350
OST680606	10	3/8'	9/16'	3/8'	29	31	19	350
OST680806	12	1/2'	3/4'	3/8'	31,8	31	19	350
OST680808	12	1/2'	3/4'	1/2'	33,7	37,3	22	350
OST681008	14	-	7/8'	1/2'	36,8	37,3	22	350
OST681008	15	-	7/8'	1/2'	36,8	37,3	22	350
OST681008	16	5/8'	7/8'	1/2'	36,8	37,3	22	350
OST681212	18	-	1 1/16'	3/4'	42,2	40,4	27	350
OST681212	20	3/4'	1 1/16'	3/4'	42,2	40,4	27	350
OST681616	25	1'	1 5/16'	1'	46	50	33	280

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 NPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
OST682020	30	-	1 5/8'	1 1/4'	52,3	59,6	41	210
OST682020	32	1 1/4'	1 5/8'	1 1/4'	52,3	59,6	41	210
OST682424	38	1 1/2'	1 7/8'	1 1/2'	59,2	67,1	48	140