



## Trójnik Typ: St. 69

Liczba wariantów: 10

---



ZESKANUJ MNIE

## Warianty produktu

| Nr katalogowy | Ø R mm | Ø R cal | Ø R-UNF JIC<br>37° cal | Ø R2 BSPT<br>cal | B mm | B2 mm | CH mm | Ciśnienie pracy<br>bar |
|---------------|--------|---------|------------------------|------------------|------|-------|-------|------------------------|
| ST.69.04.02   | 6      | 1/4'    | 7/16'                  | 1/8'             | 22,6 | 19,8  | 11    | 350                    |
| ST.69.05.02   | 8      | 5/16'   | 1/2'                   | 1/8'             | 24,1 | 19,8  | 13    | 350                    |
| ST.69.06.04   | 10     | 3/8'    | 9/16'                  | 1/4'             | 26,9 | 27,7  | 14    | 350                    |
| ST.69.08.06   | 12     | 1/2'    | 3/4'                   | 3/8'             | 31,8 | 31    | 19    | 350                    |
| ST.69.10.08   | 14     | -       | 7/8'                   | 1/2'             | 36,8 | 37,3  | 22    | 350                    |
| ST.69.10.08   | 15     | -       | 7/8'                   | 1/2'             | 36,8 | 37,3  | 22    | 350                    |
| ST.69.10.08   | 16     | 5/8'    | 7/8'                   | 1/2'             | 36,8 | 37,3  | 22    | 350                    |
| ST.69.12.12   | 18     | -       | 1 1/16'                | 3/4'             | 42,2 | 40,4  | 27    | 350                    |
| ST.69.12.12   | 20     | 3/4'    | 1 1/16'                | 3/4'             | 42,2 | 40,4  | 27    | 350                    |
| ST.69.16.16   | 25     | 1'      | 1 5/16'                | 1'               | 46   | 50    | 33    | 280                    |