


Trójnik Typ: St. 73

Liczba wariantów: 13



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 NPT cal	B mm	B2 mm	CH mm	Ciśnienie pracy bar
ST.73.04.02	6	1/4'	7/16'	1/8'	27,4	16,8	14	350
ST.73.04.04	6	1/4'	7/16'	1/4'	31	22,4	19	350
ST.73.05.02	8	5/16'	1/2'	1/8'	27,4	16,8	14	350
ST.73.06.04	10	3/8'	9/16'	1/4'	31,2	22,4	19	350
ST.73.08.06	12	1/2'	3/4'	3/8'	36,1	25,9	22	350
ST.73.10.08	14	-	7/8'	1/2'	41,7	31,2	27	350
ST.73.10.08	15	-	7/8'	1/2'	41,7	31,2	27	350
ST.73.10.08	16	5/8'	7/8'	1/2'	41,7	31,2	27	350
ST.73.12.12	18	-	1 1/16'	3/4'	48	34,5	33	350
ST.73.12.12	20	3/4'	1 1/16'	3/4'	48	34,5	33	350
ST.73.16.16	25	1'	1 5/16'	1'	55,1	41,4	41	250
ST.73.20.20	30	-	1 5/8'	1 1/4'	59,2	43,2	48	210
ST.73.20.20	32	1 1/4'	1 5/8'	1 1/4'	59,2	43,2	48	210