


Przyłącze Kolanowe Metryczne Typ: Tn 514 M

Liczba wariantów: **22**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	L1 mm	L2 mm	I mm	Ø F mm	Ø N mm	CH1 mm	CH2 mm	CH3 mm	Waga 100 szt. kg
IS-514MLLO403	LL	4	250	21,5	11,5	18,5	8,5	10x1	15	10	11	14	2,9
IS-514MLLO603	LL	6	250	25	13	16,5	8,5	10x1	15	12	14	14	3,1
IS-514MLLO607	LL	6	250	25	13	21	11	12x1,5	18	12	14	17	4,9
IS-514MLO06	L	6	315	29	14	19	8,5	10x1	15	14	14	14	6,5
IS-514MLO08	L	8	315	31	16	21	11	12x1,5	18	17	14	17	6,7
IS-514MLO10	L	10	315	32	17	24	11	14x1,5	20	19	19	19	8,7
IS-514MLO12	L	12	250	34	19	24,5	11,5	16x1,5	23	22	19	22	9,6
IS-514MLO15	L	15	250	36	21	28,5	12,5	18x1,5	25	27	22	24	22,5
IS-514MLO18	L	18	250	40	24	32,5	12,5	22x1,5	28	32	27	27	28,5
IS-514MLO22	L	22	160	44	28	34	15,5	27x2	33	36	33	32	55,2
IS-514MLO28	L	28	160	47	31	38,5	15,5	33x2	42	41	41	41	63,5
IS-514MLO35	L	35	160	59	38	46,5	15,5	42x2	51	50	48	50	83
IS-514MLO42	L	42	160	61	38	48	17	48x2	56	60	48	55	91,5

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L mm	L1 mm	L2 mm	I mm	Ø F mm	Ø N mm	CH1 mm	CH2 mm	CH3 mm	Waga 100 szt. kg
IS-514MSO06	S	6	400	30,5	15,5	22	11	12x1,5	18	17	14	17	7,5
IS-514MSO08	S	8	400	33	18	25	11	14x1,5	20	19	19	19	9
IS-514MSO10	S	10	400	34	18	25,5	12,5	16x1,5	23	22	19	22	9,9
IS-514MSO12	S	12	400	38	22	29	14	18x1,5	25	24	22	24	22,5
IS-514MSO16	S	16	400	43	25	35,5	14,4	22x1,5	28	30	27	27	28,5
IS-514MSO20	S	20	400	49	28	37,5	16	27x2	33	36	33	32	57,2
IS-514MSO25	S	25	315	54,5	30,5	41	16	33x2	42	46	41	41	75,5
IS-514MSO30	S	30	250	62	36	50	18	42x2	51	50	48	50	91,5
IS-514MSO38	S	38	200	65	34	49	20	48x2	56	60	48	55	102,5