



Złącze Proste Metryk / Nakrętka Orfs Rk2170 Iso 6149-2

Liczba wariantów: **17**



ZESKANUJ MNIE

Warianty produktu

Kod towaru	T Ø mm	T Ø cal	F	F1	A mm	B mm	D mm	D1 mm	CH mm	CH1 mm	Ciśnienie robocze bar	Ciśnienie max bar
RK2170-06-12	6	1/4	9/16-18	M12x1,5	37,2	26,2	4,2	4,2	17	19	400	530
RK2170-08-14	8	5/16	11/16-16	M14x1,5	39,2	28,2	6,5	4	19	22	400	530
RK2170-08-16	8	5/16	11/16-16	M16x1,5	40,7	28,2	6,5	6,5	22	22	400	530
RK2170-10-14	10	3/8	11/16-16	M14x1,5	39,2	28,2	6,5	4	19	22	400	530
RK2170-10-16	10	3/8	11/16-16	M16x1,5	40,7	28,2	6,5	6,5	22	22	400	530
RK2170-12-16	12	1/2	13/16-16	M16x1,5	47,8	35,3	9,1	7	22	24	400	530
RK2170-14-22	14	-	1-14	M22x1,5	52,8	37,8	11,5	11,5	27	30	400	530
RK2170-15-22	15	-	1-14	M22x1,5	52	38	11,5	11,5	27	30	400	530
RK2170-16-22	16	5/8	1-14	M22x1,5	52	38	11,5	11,5	27	30	400	530
RK2170-18-27	18	-	1-3/16-12	M27x2	59,7	41,9	13,9	13,9	32	36	400	530
RK2170-20-27	20	3/4	1-3/16-12	M27x2	59,7	41,9	13,9	13,9	32	36	400	530
RK2170-22-33	22	-	1-7/16-12	M33x2	67,5	49	20	20	41	46	400	530
RK2170-25-33	25	1	1-7/16-12	M33x2	67,5	49	20	20	41	46	400	530

Kod towaru	T Ø mm	T Ø cal	F	F1	A mm	B mm	D mm	D1 mm	CH mm	CH1 mm	Ciśnienie robocze bar	Ciśnienie max bar
RK2170-28-42	28	-	1-11/16-12	M42x2	68	49	26	26	50	50	250	330
RK2170-32-42	32	1 1/4	1-11/16-12	M42x2	68	49	26	25	50	50	250	330
RK2170-35-48	35	-	2-12	M48x2	70,5	49	32	32	55	60	250	330
RK2170-38-48	38	1 1/2	2-12	M48x2	70,5	49	32	32	55	60	250	330