



Złącze Proste Metryk / Nakrętka Orfs Rk2175 Iso 3852-1

Liczba wariantów: **16**



ZESKANUJ MNIE

Warianty produktu

Kod towaru	T Ø mm	T Ø cal	F	F1	A mm	B mm	D mm	D1 mm	CH mm	CH1 mm	Ciśnienie robocze bar	Ciśnienie max bar
RK2175-06-12	6	1/4	9/16-18	M12x1,5	38,2	26,2	4,2	4,2	17	19	400	530
RK2175-08-14	8	5/16	11/16-16	M14x1,5	40,2	28,2	6,5	5	19	22	400	530
RK2175-10-14	10	3/8	11/16-16	M14x1,5	40,2	28,2	6,5	5	19	22	400	530
RK2175-12-16	12	1/2	13/16-16	M16x1,5	47,3	35,3	9,1	7	22	24	400	530
RK2175-14-22	14	-	1-14	M22x1,5	51,8	37,5	11,5	11,5	27	30	400	530
RK2175-15-22	15	-	1-14	M22x1,5	51,8	37,5	11,5	11,5	27	30	400	530
RK2175-16-22	16	5/8	1-14	M22x1,5	51,8	37,5	11,5	11,5	27	30	400	530
RK2175-18-27	18	-	1-3/16-12	M27x2	57,2	41,2	13,9	13,9	32	36	400	530
RK2175-20-27	20	3/4	1-3/16-12	M27x2	57,2	41,2	13,9	13,9	32	36	400	530
RK2175-22-33	22	-	1-7/16-12	M33x2	67	49	20	20	41	46	400	530
RK2175-25-33	25	1	1-7/16-12	M33x2	67	49	20	20	41	46	400	530
RK2175-28-42	28	-	1-11/16-12	M42x2	69	49	25	25	50	50	250	330
RK2175-30-42	30	-	1-11/16-12	M42x2	69	49	25	25	50	50	250	330

Kod towaru	T Ø mm	T Ø cal	F	F1	A mm	B mm	D mm	D1 mm	CH mm	CH1 mm	Ciśnienie robocze bar	Ciśnienie max bar
RK2175-32-42	32	1 1/4	1-11/16-12	M42x2	69	49	25	25	50	50	250	330
RK2175-35-48	35	-	2-12	M48x2	71	49	32	32	55	60	250	330
RK2175-38-48	38	1 1/2	2-12	M48x2	71	49	32	32	55	60	250	330